

INDUSTRIAL COMPONENT DATA

+IZM-SR110AD 122746 EATON ELECTRIC Spring release, 110-127VAC/DC

Brand: EATON - MOELLER | Manufacturer Part Number: +IZM-SR110AD



Manufacturer	EATON - MOELLER
MPN / Reference	+IZM-SR110AD
Catalog number	122746
Category	Shunt release (for power circuit breaker)
Minimum order	1 Pcs
Document ID	EO-F582F2B9BE
Generated	2026-08-02

Product Overview

Spring release, 110-127VAC/DC

Closing release, Accessories, 4000 to 6300 A, Voltage release, Closing releases, Standard/Approval: IEC, A closing release can be combined with a shunt release and an undervoltage release or with an undervoltage release or with a second shunt release., Rated control voltage: Us 110 - 125 DC, 110 - 127 AC V, For use with: IZM20, 32, 40, 63..., IN20, 32,40, 63..., If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers IZM

Additional Product Information

Spring release, 110-127VAC/DC Closing release, Accessories, 4000 to 6300 A, Voltage release, Closing releases, Standard/Approval: IEC, A closing release can be combined with a shunt release and an undervoltage release or with an undervoltage release or with a second shunt release., Rated control voltage: Us 110 - 125 DC, 110 - 127 AC V, For use with: IZM20, 32, 40, 63..., IN20, 32,40, 63..., If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71 [Delivery program

Product range Accessories Current Range 4000 to 6300 A Accessories Voltage release Accessories Closing releases Standard/Approval IEC A closing release can be combined with a shunt release and an undervoltage release or with an undervoltage release or with a second shunt release. Rated control voltage [Us] 110 - 125 DC 110 - 127 AC V For use with IZM20, 32, 40, 63... IN20, 32,40, 63... Instructions If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection.

Order separately if required. Terminal assignment page 71 , Technical data

Rated control voltage [Us] AC 50/60 Hz [Us] 110 - 127 V DC [Us] 110 - 125 V Power consumption AC (pick-up 450) VA DC (pick-up 450) W Circuit-breaker response time at Us 40 ms Operating range Pick-up voltage [Pick-up] According to the IEC standard x Uc , Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C]

ETIM...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZM-SR110AD with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.