

## INDUSTRIAL COMPONENT DATA

# +IZM-SR24DC 122744 EATON ELECTRIC Spring release, 24VDC

Brand: EATON - MOELLER | Manufacturer Part Number: +IZM-SR24DC



|                 |                                           |
|-----------------|-------------------------------------------|
| Manufacturer    | EATON - MOELLER                           |
| MPN / Reference | +IZM-SR24DC                               |
| Catalog number  | 122744                                    |
| Category        | Shunt release (for power circuit breaker) |
| Minimum order   | 1 Pcs                                     |
| Document ID     | EO-82DA94A17A                             |
| Generated       | 2026-08-03                                |

## Product Overview

Spring release, 24VDC

Closing release, Accessories, 4000 to 6300 A, Voltage release, Closing releases, Standard/Approval: IEC, A closing release can be combined with a shunt release and an undervoltage release or with an undervoltage release or with a second shunt release., Rated control voltage: Us 24 DC V, For use with: IZM20, 32, 40, 63..., IN20, 32,40, 63..., If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                        |
|--------------|----------------------------------------|
| Catalog path | EATON - MOELLER > Circuit Breakers IZM |
|--------------|----------------------------------------|

## Additional Product Information

Spring release, 24VDC Closing release, Accessories, 4000 to 6300 A, Voltage release, Closing releases, Standard/Approval: IEC, A closing release can be combined with a shunt release and an undervoltage release or with an undervoltage release or with a second shunt release., Rated control voltage: Us 24 DC V, For use with: IZM20, 32, 40, 63..., IN20, 32,40, 63..., If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71 [ Delivery program

Product range Accessories Current Range 4000 to 6300 A Accessories Voltage release Accessories Closing releases Standard/Approval IEC A closing release can be combined with a shunt release and an undervoltage release or with an undervoltage release or with a second shunt release. Rated control voltage [Us] 24 DC V For use with IZM20, 32, 40, 63... IN20, 32,40, 63... Instructions If ordered separately a secondary terminal unit IZM-SEC-... is necessary for connection. Order separately if required. Terminal assignment page 71 , Technical data

Rated control voltage [Us] DC [Us] 24 V Power consumption DC (pick-up 250) W Circuit-breaker response time at Us 40 ms

Operating range Pick-up voltage [Pick-up] According to the IEC standard x  $U_c$  , Design verification as per IEC/EN 61439

Operating ambient temperature min. -25 °C Operating ambient temperature max. +70 °C ]

ETIM for 122744 Low-voltage industrial controls and switchgear (EC001023)

Feature Name

Feature Value

Suitable...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +IZM-SR24DC with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.