

INDUSTRIAL COMPONENT DATA

LS-XS 266133 Y7-266133 EATON ELECTRIC Spring-rod actuator

Brand: EATON - MOELLER | Manufacturer Part Number: LS-XS



Manufacturer	EATON - MOELLER
MPN / Reference	LS-XS
Catalog number	Y7-266133
Category	Drive head for position switches/hinge switches
Minimum order	5 Pcs
Document ID	EO-FD2D8C1595
Generated	2026-08-04

Product Overview

Spring-rod actuator

LS-XS

Eaton Moeller® series LS Spring-rod actuator

Operating head for LS-Titan position switch, IEC EN 60947-5-1, high degree of protection IP66, device for world markets, modular system, easy mounting technology, operating heads can be attached in any 4 directions and snapped-on simple, quick and safely using the bayonet fitting. Spring-rod actuator not suitable for safety functions use only with snap-action contact.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Position Switches
--------------	-------------------------------------

Additional Product Information

General specifications

Product Name Eaton Moeller® series LS Spring-rod actuator Catalog Number 266133 Model Code LS-XS EAN 4015082661335 Product Length/Depth 25 mm Product Height 120 mm Product Width 25 mm Product Weight 0.016 kg

Compliances CE Marked Certifications IEC 60947-5

EN 60947-5

UL 508

CSA Std. C22.2 No. 14

CSA Class No.: 3211-03

CSA File No.: 012528

CSA-C22.2 No. 14

CE

UL

UL File No.: E29184

CSA

IEC/EN 60947-5

UL Category Control No.: NKCR Catalog Notes Up to -25 °C in conjunction with LS-S...-CC basic device Features & Functions

Features The operating head can be rotated 90° to enable adaptation to the specified approach direction

Only permissible with snap-action contact General

Product category Spring-rod actuator Type Operating heads Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 70 °C Actuator

Actuator type Spring-rod Design verification

Equipment heat dissipation, current-dependent P_{vid} 0 W Heat dissipation capacity P_{diss} 0 W Heat dissipation per pole, current-dependent P_{vid} 0 W Rated operational current for specified heat dissipation (I_n) 0 A Static heat dissipation, non-current-dependent P_{vs} 0 W 10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1

Verification of thermal stability of enclosures Meets the product standard's requirements. 10.2.3.2 Verification of resistance of insulating materials to normal heat Meets the product standard's requirements. 10.2.3.3 Resi...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / LS-XS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.