

INDUSTRIAL COMPONENT DATA

SPRT12-264/4-AX 183184 EATON ELECTRIC Combined arrester, transient voltage surge suppression T1&T2

Brand: EATON - MOELLER | Manufacturer Part Number: SPRT12-264/4-AX



Manufacturer	EATON - MOELLER
MPN / Reference	SPRT12-264/4-AX
Catalog number	183184
Category	Combined arrester for power supply systems
Minimum order	1 Pcs
Document ID	EO-CE7175E68E
Generated	2026-08-05

Product Overview

Combined arrester, transient voltage surge suppression T1&T2;

Multi-pole combined arrester, type 1 as specified in EN 61643-11, spark-gap-based, consisting of base and plug-in protection modules. Maximum system availability ensured by means of RADAX Flow follow current limiting. Allows for end-device protection. For protecting low-voltage consumer installations from overvoltages, even in the event of direct lightning strikes. Application according to lightning protection zone approach at interfaces 0A- 2.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Modular Switchgear - Industrial
--------------	---

Additional Product Information

Combined arrester, transient voltage surge suppression T1&T2; Multi-pole combined arrester, type 1 as specified in EN 61643-11, spark-gap-based, consisting of base and plug-in protection modules. Maximum system availability ensured by means of RADAX Flow follow current limiting. Allows for end-device protection. For protecting low-voltage consumer installations from overvoltages, even in the event of direct lightning strikes. Application according to lightning protection zone approach at interfaces 0A- 2. [Delivery program

Products Surge arresters Application field Residential buildings

Utility buildings

Open areas , Technical data ETIM 6.0

Earthing, lightning and surge protection (EG000021) / Combined arrester for power supply systems (EC001457) Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Combined lightning current/surge arrester f. power supply s. () [ACN284008]

System configuration DC No System configuration IT Yes System configuration TN Yes System configuration TN-C No
System configuration TN-C-S Yes System configuration TN-S Yes System configuration TT Yes System configuration other
Yes Number of poles 4 Lightning impulse current (10/350) 100 kA Max. continuous voltage AC 264 V Max. continuous
voltage DC 0 V Nominal voltage AC 230 V Nominal voltage DC 0 V Max. PV-voltage 0 V Voltage protection level 1.5 kV
Voltage protection level L-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPRT12-264/4-AX with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.