

INDUSTRIAL COMPONENT DATA

SPX400A0-4A2B1 138618 EATON ELECTRIC Frequency converter SPX 3/3 480 V 250 kW Vector Control Dynamic IP00 EM..

Brand: EATON - MOELLER | Manufacturer Part Number: SPX400A0-4A2B1



Manufacturer	EATON - MOELLER
MPN / Reference	SPX400A0-4A2B1
Catalog number	138618
Category	Frequency converter less than 1 kV
Minimum order	1 Pcs
Document ID	EO-86E8631CF4
Generated	2026-08-02

Product Overview

Frequency converter SPX 3/3; 480 V 250 kW; Vector Control Dynamic; IP00; EMC Filter; Transistor braking
Frequency converter; High performance; 590 A; 315 kW; IP00; 400 V AC; Braking transistor
Variable frequency drive, 400 V AC, 3-phase, 250 kW, IP00, Brake chopper, OLED display, FR11

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Eaton Frequency Converters
--------------	--

Additional Product Information

Variable frequency drive, 400 V AC, 3-phase, 250 kW, IP00, Brake chopper, OLED display, FR11
Variable frequency drive, Part group reference (e.g. DIL): SPX, Rated operational voltage: $U_e = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Output voltage with V_e : $U_2 = 400 \text{ V AC}$, 3-phase, 480 V AC, 3-phase, 500 V AC, 3-phase, Mains voltage (50/60Hz): $U_{LN} = 380 (-15\%) - 500 (+10\%) \text{ V}$, Rated operational current At 150% overload: $I_e = 520 \text{ A}$, Rated operational current At 110% overload: $I_e = 590 \text{ A}$, Note: Overload cycle for 60 s every 600 s, Assigned motor rating Note: For AC motors with internal and external ventilation with 50 Hz / 60 Hz, Overload cycle for 60 s every 600 s, at 400 V, 50 Hz, Assigned motor rating 150 % Overload: $P = 250 \text{ kW}$, 110 % Overload: $P = 315 \text{ kW}$, 150 % Overload: $I_M = 437 \text{ A}$, 110 % Overload: $I_M = 544 \text{ A}$, Assigned motor rating Note: at 440 - 480 V, 60 Hz, Assigned motor rating 150 % Overload: $P = 400 \text{ HP}$, 110 % Overload: $P = 500 \text{ HP}$, Assigned motor rating 150 % Overload: $I_M = 477 \text{ A}$, 110 % Overload: $I_M = 590 \text{ A}$, Degree of Protection: IP00, Fieldbus connection (optional): PROFIBUS-DP, LonWorks, CANopen®, DeviceNet, Modbus-TCP, BACnet/IP, Fitted with: Brake chopper, OLED display, Frame size: FR11, Standards: Specification for

general requirements: IEC/EN 61800-2, EMC requirements: IEC/EN 61800-3, Safety requirements: IEC/EN 61800-5-1 Delivery program

Product range Variable frequency drives Part group reference (e.g. DIL) SPX Rated operational voltage [U_e] 400 V AC, 3-pha...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPX400A0-4A2B1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.