

INDUSTRIAL COMPONENT DATA

NHI-E-01-PKZ0-C 229682 XTPAXFAC01 EATON ELECTRIC

Standard auxiliary contact, 1 N/C, flush mounting, spring c..

Brand: EATON - MOELLER | Manufacturer Part Number: NHI-E-01-PKZ0-C



Manufacturer	EATON - MOELLER
MPN / Reference	NHI-E-01-PKZ0-C
Catalog number	XTPAXFAC01
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-736AC515DC
Generated	2026-08-05

Product Overview

Standard auxiliary contact, 1 N/C, flush mounting, spring clamp connection

Front Auxiliary Contact 1 NC Snap-On Connection

Standard auxiliary contact, Contacts N/C = Normally closed: 1 NC, For use with: PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

EL-Nummer (Norway)4315179Standard auxiliary contact, 1 N/C, flush mounting, spring clamp connectionStandard auxiliary contact, Contacts N/C = Normally closed: 1 NC, For use with: PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKEDelivery program

Product rangeAccessoriesAccessoriesStandard auxiliary contactCan be fitted to the front

Terminal designation differs to that of an auxiliary contact that can be fitted to the sideContactsN/C = Normally closed1

NCContact diagramContact sequenceConnection techniqueSpring-loaded terminalsFor use withPKZ0(4) standard auxiliary contactsFor use withPKZM01

PKZM0

PKZM4

PKZM0-T

PKM0

PKENotesCan be fitted to:

Motor protective circuit-breaker

Transformer-protective circuit-breaker

Motor protective circuit breaker for starter combinations

(From serial number 01)

Cannot be used for motor starter combinations type MSC...

45 mm (PKZM0 and PKZM01) or 55 mm (PKZM4) widths of the motor-protective circuit-breakers remain unchanged. Technical data

Auxiliary contacts Rated impulse withstand voltage [Uimp] 4000 V AC Overvoltage category/pollution degree III/3 Rated operational voltage [Ue] [Ue] 440 V AC Rated operational voltage [Ue] [Ue] 250 V DC Safe isolation to EN 61140 Between auxiliary contacts and main contacts 690 V AC Rated operational current [Ie] AC-15 220 - 240 V [Ie] 1 A Rated operational current [Ie] DC-13 L/R - 100 ms 24 V [Ie] 2 A Lifespan Lifespan, mechanical [Operations] > 0.1 x 10⁶ Lifespan Lifespan, electrical [Operations] 0.1 x 10⁶ Control circuit reliability [Failure ra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI-E-01-PKZ0-C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.