

INDUSTRIAL COMPONENT DATA

NHI-E-10-PKZ0 082884 Y7-82884 EATON ELECTRIC Standard auxiliary contact, 1N/O, flush mounting, screw connect..

Brand: EATON - MOELLER | Manufacturer Part Number: NHI-E-10-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	NHI-E-10-PKZ0
Catalog number	Y7-82884
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-08180EB15D
Generated	2026-08-05

Product Overview

Standard auxiliary contact, 1N/O, flush mounting, screw connection

Front Auxiliary Contact 1 NO Screw Connection

Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, Can be fitted to the front, Screw terminals

Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, For use with: DILM

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Circuit Breakers PKZ**

Additional Product Information

General specifications

Product Name Eaton Moeller® series NHI Accessory Standard auxiliary contact Catalog Number 082884 Model Code NHI-E-10-PKZ0 EAN 4015080828846 Product Length/Depth 12 mm Product Height 35 mm Product Width 45 mm Product Weight 0.011 kg Certifications CE

CSA File No.: 165628

CSA

IEC/EN 60947-4-1

UL Category Control No.: NLRV

CSA Class No.: 3211-05

CSA-C22.2 No. 14

UL File No.: E36332

UL

UL 508 Catalog Notes Can be fitted to the front. Terminal designation differs to that of an auxiliary contact that can be fitted to the side General

Lifespan, electrical 100,000 Operations Lifespan, mechanical 100,000 Operations Model Top mounting Mounting method Front fastening Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 4000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 0.75 - 1.5 mm² Terminal capacity (solid/stranded AWG) 18 - 16, Screw terminals Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 1 A Rated operational current (Ie) at DC-13, 24 V 2 A Rated operational voltage (Ue) at AC - max 440 V Rated operational voltage (Ue) at DC - max 250 V Safe isolation 440 V, Between auxiliary contacts and main contacts, According to EN 61140 Short-circuit protection rating without welding 10 A gG/gL...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI-E-10-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.