

INDUSTRIAL COMPONENT DATA

+NHI-E-10-PKZ0 082885 Y7-82885 EATON ELECTRIC Standard auxiliary contact, 1N/O, flush mounting, screw connec..

Brand: EATON - MOELLER | Manufacturer Part Number: +NHI-E-10-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	+NHI-E-10-PKZ0
Catalog number	Y7-82885
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-016E57A163
Generated	2026-08-06

Product Overview

Standard auxiliary contact, 1N/O, flush mounting, screw connection. Can only be sold assembled.

Front auxiliary contact. 1 NO. Screw connection. Factory assembly

Standard auxiliary contact, 1N/O, flush mounting, screw connection

Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ0 Accessory Standard auxiliary contact Catalog Number 082885 Model Code +NHI-E-10-PKZ0 EAN 4015080828853 Product Length/Depth 12 mm Product Height 35 mm Product Width 45 mm Product Weight 0.011 kg Certifications UL Category Control No.: NLRV

CSA

CSA-C22.2 No. 14

CSA File No.: 165628

CSA Class No.: 3211-05

UL

UL 508

UL File No.: E36332

CE

IEC/EN 60947-4-1 General

Lifespan, electrical 100,000 Operations Lifespan, mechanical 100,000 Operations Model Top mounting Mounting method Front fastening Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 4000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities Terminal capacity (solid/flexible with ferrule) 0.75 - 1.5 mm² Terminal capacity (solid/stranded AWG) 18 - 16, Screw terminals Electrical rating Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 1 A Rated operational current (Ie) at DC-13, 110 V 0.5 A Rated operational current (Ie) at DC-13, 24 V 2 A Rated operational current (Ie) at DC-13, 60 V 1 A Rated operational voltage (Ue) at AC - max 400 V Rated operational voltage (Ue) at DC - max 250 V Safe isolation 440 V, Between auxiliary contacts and main contacts, According to EN 61140 Short-circuit protection rating without welding 10 A gG/gL, Fuse, Auxiliary contacts Co...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +NHI-E-10-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.