

INDUSTRIAL COMPONENT DATA

NHI-E-10L-PKZ0 107040 Y7-107040 EATON ELECTRIC

Standard auxiliary contact, 1N/O, flush mounting, SmartWire-DT

Brand: EATON - MOELLER | Manufacturer Part Number: NHI-E-10L-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	NHI-E-10L-PKZ0
Catalog number	Y7-107040
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-A5AE2B9C2A
Generated	2026-08-06

Product Overview

Standard auxiliary contact, 1N/O, flush mounting, SmartWire-DT

NHI-E-10L-PKZ0

Eaton Moeller® series NHI Standard auxiliary contact, 1N/O, flush mounting, SmartWire-DT

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series NHI Accessory Standard auxiliary contact Catalog Number 107040 Model Code NHI-E-10L-PKZ0 EAN 4015081068081 Product Length/Depth 12 mm Product Height 35 mm Product Width 45 mm Product Weight 0.019 kg Certifications CE Features & Functions

Electric connection type Screw connection General

Lifespan, electrical 100,000 Operations Lifespan, mechanical 100,000 Operations Model Top mounting Mounting method Front fastening Overvoltage category III Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 4000 V AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 0.75 - 1.5 mm² Terminal capacity (solid/stranded AWG) 18 - 16, Screw terminals Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 1 A Rated operational current (Ie) at DC-13, 24 V 2 A Rated operational voltage (Ue) at AC - max 440 V Rated operational voltage (Ue) at DC - max 250 V Safe isolation 440 V, Between auxiliary contacts and main contacts, According to EN 61140 Short-circuit protection rating without welding 10 A gG/gL, Fuse, Auxiliary contacts Communication
Connection type Screw connection Contacts
Control circuit reliability $< 2 \times 10^{-6}$, < 1 failure at 100,000,000 Operations (at Ue = 24 V DC, Umin = 17 V, Imin = 5.4 mA) Number of contacts (change-over contacts) 0 Number of...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI-E-10L-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.