

INDUSTRIAL COMPONENT DATA

NHI-E-11-PKZ0 082882 Y7-82882 EATON ELECTRIC Standard auxiliary contact, 1N/O+1N/C, flush mounting, screw co..

Brand: EATON - MOELLER | Manufacturer Part Number: NHI-E-11-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	NHI-E-11-PKZ0
Catalog number	Y7-82882
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-25131EE67E
Generated	2026-08-06

Product Overview

Standard auxiliary contact, 1N/O+1N/C, flush mounting, screw connection

Front auxiliary contact 1 NO + 1 NC Screw connection

Eaton Moeller® series NHI Standard auxiliary contact, NHI-E, 1 N/O, 1 NC, Can be fitted to the front, Screw terminals

Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with:

PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Circuit Breakers PKZ

Additional Product Information

General specifications

Product Name Eaton Moeller® series NHI Accessory Standard auxiliary contact

Catalog Number 082882

Model Code NHI-E-11-PKZ0

EAN 4015080828822

Product Length/Depth 12 mm

Product Height 35 mm

Product Width 45 mm

Product Weight 0.016 kg

Certifications CE

UL Category Control No.: NLRV

CSA

CSA-C22.2 No. 14

UL File No.: E36332

CSA File No.: 165628

IEC/EN 60947-4-1

UL 508

CSA Class No.: 3211-05

UL

Catalog Notes Can be fitted to the front. Terminal designation differs to that of an auxiliary contact that can be fitted to the side

General

Lifespan, electrical 100,000 Operations

Lifespan, mechanical 100,000 Operations

Model Top mounting

Mounting method Front fastening

Overvoltage category III

Pollution degree 3

Product category Accessories

Rated impulse withstand voltage (Uimp) 4000 V AC

Used with Motor protective circuit-breaker

Climatic environmental conditions

Ambient operating temperature - min -25 °C

Ambient operating temperature - max 55 °C

Terminal capacities

Terminal capacity (solid/flexible with ferrule) 0.75 - 1.5 mm²

Terminal capacity (solid/stranded AWG) 18 - 16, Screw terminals

Electrical rating

Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 1 A

Rated operational current (Ie) at DC-13, 24 V 2 A

Rated operational voltage (Ue) at AC - max 440 V

Rated operational voltage (Ue) at DC - max 250 V

Safe isolation 440 V, Between auxiliary contacts and main contacts, According to EN 61140

Short-circuit protection rating without welding 10 A gG/gL...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI-E-11-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.