

INDUSTRIAL COMPONENT DATA

NHI11-PKZ0 072896 Y7-72896 EATON ELECTRIC Standard auxiliary contact, 1N/O+1N/C, screw connection

Brand: EATON - MOELLER | Manufacturer Part Number: NHI11-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	NHI11-PKZ0
Catalog number	Y7-72896
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-B0B7FBC462
Generated	2026-08-06

Product Overview

Standard auxiliary contact, 1N/O+1N/C, screw connection

Side auxiliary contact 1 NO + 1 NC Screw connection

Eaton Moeller® series NHI Standard auxiliary contact, 1 N/O, 1 NC, Can be retrofitted on the right side of motor-protective circuit-breakers, Screw terminals

Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series NHI Accessory Standard auxiliary contact Catalog Number 072896 Model Code NHI11-PKZ0 EAN 4015080728962 Product Length/Depth 68 mm Product Height 90 mm Product Width 15 mm Product Weight 0.033 kg Certifications CE

UL 508

CSA File No.: 165628

UL

UL File No.: E36332

IEC/EN 60947-4-1

CSA-C22.2 No. 14

UL Category Control No.: NLRV

CSA

CSA Class No.: 3211-05 Catalog Notes Can be retrofitted on the right side of motor-protective circuit-breakers Features & Functions

Electric connection type Screw connection Features Interlocked opposing contacts General

Lifespan, electrical 50,000 Operations Model Top mounting Mounting method Side mounting Overvoltage category III

Pollution degree 3 Product category Accessories Rated impulse withstand voltage (Uimp) 6000 V AC Used with Motor protective circuit-breaker Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 55 °C Terminal capacities

Terminal capacity (solid/flexible with ferrule) 0.75 - 1.5 mm² Terminal capacity (solid/stranded AWG) 18 - 14, Screw terminals Electrical rating

Rated operational current (Ie) 1 A at AC-15, 440 V 500 V Rated operational current (Ie) at AC-15, 220 V, 230 V, 240 V 3.5 A

Rated operational current (Ie) at AC-15, 380 V, 400 V, 415 V 2 A Rated operational current (Ie) at DC-13, 110 V 0.5 A

Rated operational current (Ie) at DC-13, 220 V, 230 V 0.25 A Rated operational current (Ie) at DC-13, 24 V 2....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI11-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.