

INDUSTRIAL COMPONENT DATA

+NHI11-PKZ0 073233 Y7-73233 EATON ELECTRIC Standard auxiliary contact, 1N/O+1N/C, screw connection. Únicamen..

Brand: EATON - MOELLER | Manufacturer Part Number: +NHI11-PKZ0



Manufacturer	EATON - MOELLER
MPN / Reference	+NHI11-PKZ0
Catalog number	Y7-73233
Category	Auxiliary contact block
Minimum order	1 Pcs
Document ID	EO-2EC0BAEF29
Generated	2026-08-06

Product Overview

Standard auxiliary contact, 1N/O+1N/C, screw connection. Únicamente se puede vender montada.

Lateral auxiliary contact; 1 NO + 1 NC; Screw connection; Mounting in

Standard auxiliary contact, 1N/O+1N/C, screw connection

Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Circuit Breakers PKZ
--------------	--

Additional Product Information

Standard auxiliary contact, 1N/O+1N/C, screw connectionStandard auxiliary contact, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC

General specificationsProduct nameEaton Moeller® series PKZ0 Accessory Standard auxiliary contactPart no.+NHI11-PKZ0EAN4015080732334Product Length/Depth68 millimetreProduct height90 millimetreProduct width15 millimetreProduct weight0.034 kilogramCertificationsIEC/EN 60947-4-1

CSA

CE

CSA File No.: 165628

UL

CSA-C22.2 No. 14

UL File No.: E36332

UL Category Control No.: NLRV

CSA Class No.: 3211-05

UL 508Product TradenamePKZ0Product TypeAccessoryProduct Sub TypeStandard auxiliary contactCatalog NotesCan be combined with AGM, NHI-E ...

Cannot be used for motor starter combinations type MSC-R...Features & FunctionsElectric connection typeScrew connectionGeneral informationLifespan, electrical50,000 OperationsModelTop mountingMounting methodSide mountingOvervoltage categoryIIIPollution degree3Product categoryAccessoriesRated impulse withstand voltage (Uimp)6000 V ACUsed withMotor protective circuit-breakerClimatic environmental conditionsAmbient operating temperature - min-25 °CAmbient operating temperature - max55 °CTerminal capacitiesTerminal capacity (solid/flexible with ferrule)0.75 - 1.5 mm²Terminal capacity (solid/stranded AWG)18 - 14, Screw terminalsElectrical ratingRated operational current (Ie)1 A at AC-15, 440 V 500 VRated operational current (Ie) at AC-15, 220 V, 230 V, 240 V3.5 ARated operational current (Ie) at AC-...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / +NHI11-PKZ0 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.