

INDUSTRIAL COMPONENT DATA

NHI11-PKZ0-C 229680 XTPAXSAC11 EATON ELECTRIC

Standard auxiliary contact, 1N/O+1N/C, spring clamp connection

Brand: EATON - MOELLER | Manufacturer Part Number: NHI11-PKZ0-C



Manufacturer	EATON - MOELLER
MPN / Reference	NHI11-PKZ0-C
Catalog number	XTPAXSAC11
Category	Auxiliary contact block
Minimum order	5 Pcs
Document ID	EO-451865D1FF
Generated	2026-08-05

Product Overview

Standard auxiliary contact, 1N/O+1N/C, spring clamp connection

Side auxiliary contact 1 NO + 1 NC Snap-in connection

Standard auxiliary contact, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Motor-protective circuit-breakers PKZ (Accessories)

Additional Product Information

EL-Nummer (Norway)4315178Standard auxiliary contact, 1N/O+1N/C, spring clamp connectionStandard auxiliary contact, Contacts N/O = Normally open: 1 N/O, Contacts N/C = Normally closed: 1 NC, For use with: PKZM01, PKZM0, PKZM4, PKZM0-T, PKM0, PKEDelivery program

Product rangeAccessoriesAccessoriesStandard auxiliary contactCan be retrofitted on the right side of motor-protective circuit-breakersContactsN/O = Normally open1 N/ON/C = Normally closed1 NCContact diagramContact sequenceConnection techniqueSpring-loaded terminalsFor use withPKZ0(4) standard auxiliary contactsFor use withPKZM01

PKZM0

PKZM4

PKZM0-T

PKM0

PKENotesCan be fitted to the right of:

Motor protective circuit-breaker

Transformer-protective circuit-breaker

Motor protective circuit breaker for starter combinations

Cannot be used for motor starter combinations type MSC-R...

can be combined with AGM, NHI-E ...Technical data

Auxiliary contactsRated impulse withstand voltage [Uimp]6000 V ACOvervoltage category/pollution degreeIII/3Rated operational voltage [Ue] [Ue]500 V ACRated operational voltage [Ue] [Ue]250 V DCsafe isolation to EN 61140Between auxiliary contacts and main contacts690 V ACRated operational current [Ie]AC-15220 - 240 V [Ie]3.5 ARated operational current [Ie]AC-15380 - 415 V [Ie]2 ARated operational current [Ie]AC-15440 V 500 V [Ie]1 ARated operational current [Ie]DC-13 L/R - 100 ms24 V [Ie]2 ARated operational current [Ie]DC-13 L/R - 100 ms60 V [Ie]1 ARated operational current [Ie]DC-13 L/R - 100 ms...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / NHI11-PKZ0-C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.