

INDUSTRIAL COMPONENT DATA

BP-MN-600/12/1,75 119200 0002460732 EATON ELECTRIC

Standard-compliant "mask" distribution board, WxHxD 573 x..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-MN-600/12/1,75



Manufacturer	EATON - MOELLER
MPN / Reference	BP-MN-600/12/1,75
Catalog number	0002460732
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-BDD5DB0020
Generated	2026-08-06

Product Overview

Standard-compliant "mask" distribution board, WxHxD = 573 x 1200 x 175 mm

Standard-compliant zmaskz distribution board, IP30, BP-MN-, width 573 mm, outside height 1200 mm, front plate height 1150 mm, depth 175 mm, with MSW assembly, but without BPZ-MES mounting subrack, top adjustment plate insert, welded distribution board

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic LV systems Low voltage switchgear Catalog Number 119200 Model Code

BP-MN-600/12/1,75 EAN 4015081173372 Product Length/Depth 185 mm Product Height 1210 mm Product Width 585 mm

Product Weight 11 kg Compliances RoHS conform Delivery program

Color Gray Technical data - mechanical

Surface finishing Powder coating Material Steel Material quality Other Number of connector holes 0 Number of covers/doors

0 Number of locks 0 Built-in depth 175 mm Permissible load of the door(s) according to IEC 62208 - max 0 N Permissible

load of the enclosure according to IEC 62208 - max 0 N Permissible load of the mounting plate according to IEC 62208 -

max 0 N Installation type Floor installation possible Temperature-rise verification as per IEC 60890

Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890) 55 W Heat diss. ambient 35°C delta T: 35°C

wall mount middle encl. top (IEC 60890) 111 W Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC

60890) 57 W Heat diss. ambient 35°C delta T:20°C wall mount starting encl. top (IEC 60890) 74 W Heat diss. ambient 35°C

delta T:35°C wall mount individ. encl. top (IEC 60890) 115 W Heat diss. ambient 35°C delta T:35°C wall mount starting encl. top (IEC 60890) 149 W Thermal dissipation (Delta T = 20 K) according to IEC/TR 60890 0 W Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-MN-600/12/1,75 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.