

INDUSTRIAL COMPONENT DATA

BP-MN-1000/17/1,75 119212 0002460744 EATON ELECTRIC

Standard-compliant "mask" distribution board, WxHxD 973 ..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-MN-1000/17/1,75



Manufacturer	EATON - MOELLER
MPN / Reference	BP-MN-1000/17/1,75
Catalog number	0002460744
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-F7345CB9BC
Generated	2026-08-06

Product Overview

Standard-compliant "mask" distribution board, WxHxD = 973 x 1700 x 175 mm

Standard-compliant zmaskz distribution board, IP30, BP-MN-, width 973 mm, outside height 1700 mm, front plate height 1650 mm, depth 175 mm, with MSW assembly, but without BPZ-MES mounting subrack, top adjustment plate insert, welded distribution board

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Standard-compliant "mask" distribution board, WxHxD = 973 x 1700 x 175 mm EL-Nummer (Norway) 0002460744

Standard-compliant "mask" distribution board, IP30, BP-MN-, width 973 mm, outside height 1700 mm, front plate height 1650 mm, depth 175 mm, with MSW assembly, but without BPZ-MES mounting subrack, top adjustment plate insert, welded distribution board [Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV] 146 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosure for wall mounting [PV] 142 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Middle enclosure for wall mounting [PV] 138 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV] 293 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35 degrees in top of the enclosure, calculated as per IEC 60890Starting enclosure for wall mounting [PV] 284 W Heat dissipation, at an ambient temperature of 35°C, delta T: 35

degrees in top of the enclosure, calculated as per IEC 60890 Middle enclosure for wall mounting [PV] 277 W IEC/EN 61439 design veri...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-MN-1000/17/1,75 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.