

INDUSTRIAL COMPONENT DATA

**SDAINLM22(230V50HZ,240V60HZ) 278336 Y7-278336 EATON
ELECTRIC Star-delta contactor combination, 11kW/400V/AC3**

Brand: EATON - MOELLER | Manufacturer Part Number: SDAINLM22(230V50HZ,240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	SDAINLM22(230V50HZ,240V60HZ)
Catalog number	Y7-278336
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-EEDB377CF3
Generated	2026-08-06

Product Overview

Star-delta contactor combination, 11kW/400V/AC3

SDAINLM22(230V50HZ,240V60HZ)

Star-delta contactor combination, 380 V 400 V: 11 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

Star-delta contactor combination, Application: Star-delta motor starting for contactor combinations, Operating frequency: maximum 30 starts per hour, Accessories: Star-delta combinations SDAINL, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, Rated operational current AC-3 380 V 400 V: I_e= 22 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 5.5 kW, 380 V 400 V: P= 11 kW, 500 V: P= 11 kW, 660 V 690 V: P= 11 kW, Max. changeover time: 20 s, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation, Individual components of the combination Mains contactor Q11: DILM12-10, + DILA-XHI20, Delta contactor Q15: DILM12-01, + DILA-XHI20 Part no., Star contactor Q13: DILM7-01, + DILA-XHI20 Part no., Timing relay K1: ETR4-51 Part no., Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

EL-Nummer (Norway)4130486Star-delta contactor combination, 380 V 400 V: 11 kW, 230 V 50 Hz, 240 V 60 Hz, AC operationStar-delta contactor combination, Application: Star-delta motor starting for contactor combinations, Operating frequency: maximum 30 starts per hour, Accessories: Star-delta combinations SDAINL, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, Rated operational current AC-3 380 V 400 V: I_e= 22 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 5.5 kW, 380 V 400 V: P= 11 kW, 500 V: P= 11 kW, 660 V 690 V:

P= 11 kW, Max. changeover time: 20 s, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation, Individual components of the combination Mains contactor Q11: DILM12-10, + DILA-XHI20, Delta contactor Q15: DILM12-01, + DILA-XHI20 Part no., Star contactor Q13: DILM7-01, + DILA-XHI20 Part no., Timing relay K1: ETR4-51 Part no., Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging.Delivery program

Product rangeContactor combinationsApplicationStar-delta motor starting for contactor combinationsAccessoriesStar-delta combinations SDAINLUtilization categoryNAC-3: Normal AC induction motors: starting, switch off during runningNotesAlso suitable for motors with efficiency class IE3.

IE3-ready devices are identified by the logo on their packaging.DescriptionOperating frequency: maximum 30 starts per hourRated operational c...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SDAINLM22(230V50HZ,240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.