


INDUSTRIAL COMPONENT DATA

**SDAINLM140(230V50HZ,240V60HZ) 240009 Y7-240009 EATON
ELECTRIC Star-delta contactor combination, 3p, 75kW/400..**

Brand: EATON - MOELLER | Manufacturer Part Number: SDAINLM140(230V50HZ,240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	SDAINLM140(230V50HZ,240V60HZ)
Catalog number	Y7-240009
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-54FA22955B
Generated	2026-08-06

Product Overview

Star-delta contactor combination, 3p, 75kW/400V/AC3

SDAINLM140(230V50HZ,240V60HZ)

Eaton Moeller® series SDAINL Star-delta contactor combination, 380 V 400 V: 75 kW, 230 V 50 Hz, 240 V 60 Hz, AC operation

Star-delta contactor combination, Application: Star-delta motor starting for contactor combinations, Operating frequency: maximum 30 starts per hour, Accessories: Star-delta combinations SDAINL, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, Rated operational current AC-3 380 V 400 V: I_e= 140 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 37 kW, 380 V 400 V: P= 75 kW, 500 V: P= 90 kW, 660 V 690 V: P= 90 kW, Max. changeover time: 20 s, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation , Individual components of the combination Mains contactor Q11: DILM80, + DILM150-XHI31, Delta contactor Q15: DILM80, + DILM150-XHI11 Part no., Star contactor Q13: DILM50, + DILM150-XHI11 Part no., Timing relay K1: ETR4-51 Part no., Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Contactors up to 170A

Additional Product Information

General specifications

Product Name Eaton Moeller® series SDAINL contactor combination Catalog Number 240009 Model Code

SDAINLM140(230V50HZ,240V60HZ) EAN 4015082400095 Product Length/Depth 174 mm Product Height 170 mm

Product Width 258 mm Product Weight 10.01 kg Certifications CE Features & Functions

Functions Star-delta contactor General

Application Star-delta motor starting for contactor combinations Product category Contactor combinations Suitable for Also
motors with efficiency class IE3 Used with ETR4-51 Utilization category AC-3: Normal AC induction motors: starting, switch
off during running Voltage type AC Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Electrical Rating

Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 140 A Rated operational current (Ie) at AC-3, 380 V, 400 V, 415
V 140 A Rated operational current (Ie) at AC-1, 380 V, 400 V, 415 V 140 A Rated operational power at AC-3, 380/400 V, 50
Hz 75 kW Switching time

Changeover time 20 s, max. Magnet system

Duty factor 100 % Rated control supply voltage (Us) at AC, 50 Hz - min 230 V Rated control supply voltage (Us) at AC, 50
Hz - max 230 V Rated control supply voltage (Us) at AC, 60 Hz - min 240 V Rated control supply voltage (Us) at AC, 60 Hz
- max 240 V Rated control supply voltage (Us) at DC - min 0 V Rated control supply voltage (Us) at DC - max 0 V

Communication

Connection Screw terminals Contacts

Number of auxiliary contac...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SDAINLM140(230V50HZ,240V60HZ) with the required quantity to info@electricaonline.com or
use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.