

INDUSTRIAL COMPONENT DATA

SDAINLEM(230V50HZ,240V60HZ) 051840 XTSD012A10F

EATON ELECTRIC Star-delta contactor combination, 5.5kW/400V/A..

Brand: EATON - MOELLER | Manufacturer Part Number: SDAINLEM(230V50HZ,240V60HZ)



Manufacturer	EATON - MOELLER
MPN / Reference	SDAINLEM(230V50HZ,240V60HZ)
Catalog number	XTSD012A10F
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-9C973E91DA
Generated	2026-08-06

Product Overview

Star-delta contactor combination, 5.5kW/400V/AC3

Star/Triangle Contactor Combination; Screw connection; 5.5 kW; 400 V; AC-3; 230 V 50 Hz, 240 V 60 Hz

Star-delta contactor combination, Application: Star-delta motor starting for contactor combinations, Operating frequency: maximum 30 starts per hour, Accessories: Star-delta combinations SDAINL, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, Rated operational current AC-3 380 V 400 V: I_e= 12 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 4 kW, 380 V 400 V: P= 5.5 kW, 500 V: P= 5.5 kW, Max. changeover time: 30 s, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation, Individual components of the combination Mains contactor Q11: DILEM-10 + 22DILEM, Delta contactor Q15: DILEM-01 Part no., Star contactor Q13: DILEM-10 + 02DILEM Part no., Timing relay K1: DILET Part no., Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Contactors up to 170A
--------------	---

Additional Product Information

Star-delta contactor combination, 5.5kW/400V/AC3Star-delta contactor combination, Application: Star-delta motor starting for contactor combinations, Operating frequency: maximum 30 starts per hour, Accessories: Star-delta combinations SDAINL, Utilization category: NAC-3: Normal AC induction motors: starting, switch off during running, Rated operational current AC-3 380 V 400 V: I_e= 12 A, Max. rating for three-phase motors, 50 - 60 Hz AC-3 220 V 230 V: P= 4 kW, 380 V 400

V: P= 5.5 kW, 500 V: P= 5.5 kW, Max. changeover time: 30 s, Actuating voltage: 230 V 50 Hz, 240 V 60 Hz, Voltage AC/DC: AC operation, Individual components of the combination Mains contactor Q11: DILEM-10 + 22DILEM, Delta contactor Q15: DILEM-01 Part no., Star contactor Q13: DILEM-10 + 02DILEM Part no., Timing relay K1: DILET Part no., Notes: Also suitable for motors with efficiency class IE3., IE3-ready devices are identified by the logo on their packaging.Delivery program

This item will continue to be available for a limited time only and is being replaced by the following item: 278286, SDAINLM12(230V50HZ,240V60HZ)Product rangeContactor combinationsApplicationStar-delta motor starting for contactor combinationsAccessoriesStar-delta combinations SDAINLUtilization categoryNAC-3: Normal AC induction motors: starting, switch off during runningNotesAlso suitable for motors with efficiency class IE3. IE3-ready devices are identified by the logo on their packaging.DescriptionOperating frequency: maximum 30 starts....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SDAINLEM(230V50HZ,240V60HZ) with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.