

INDUSTRIAL COMPONENT DATA

T0-5-25/E 014605 Y7-14605 EATON ELECTRIC Star-delta switches, Contacts: 9, 20 A, front plate: 0-Y-D, 60 °, m..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-25/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-25/E
Catalog number	Y7-14605
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-68DF22407D
Generated	2026-08-05

Product Overview

Star-delta switches, Contacts: 9, 20 A, front plate: 0-Y-D, 60 °, maintained, flush mounting, SOND 29

Star-Triangle switch; 9 poles; 20 A; Indicator plate: 0-Y-D; 60 °; Flush mounting

Eaton Moeller® series T0 Star-delta switches, T0, 20 A, flush mounting, 5 contact unit(s), Contacts: 9, 60 °, maintained, With 0 (Off) position, 0-Y-D, SOND 29, Design number 25

Star-delta switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Notes: SOND 29, Contacts: 9, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: I_u = 20 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Star-delta switch Catalog Number 014605 Model Code T0-5-25/E EAN 4015080146056 Product Length/Depth 114 mm Product Height 48 mm Product Width 48 mm Product Weight 0.147 kg

Certifications VDE 0660

IEC/EN 60947-3

IEC/EN 60204

CE

CSA
IEC/EN 60947
UL File No.: E36332
CSA-C22.2 No. 60947-4-1-14
UL 60947-4-1
CSA-C22.2 No. 94
UL
UL Category Control No.: NLRV
CSA File No.: 012528
CSA Class No.: 3211-05 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 014605 Low-voltage industrial controls and switchgear (EC001105)
Feature Name
Feature Value
Model (EF000010)
Star-delta switch
Number of poles (EF001391)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current Iu (EF001389)
20 A
Rated operation current Ie at AC-3, 400 V (EF001392)
11.5 A
Rated operation power at AC-3, 400 V (EF001364)
5.5 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)
No

Housing mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-25/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.