

INDUSTRIAL COMPONENT DATA

T3-5-15899/Z 004121 Y7-4121 EATON ELECTRIC Star-delta switches, Contacts: 10, 32 A, front plate: 0-Y-D, 60 °.

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-15899/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-15899/Z
Catalog number	Y7-4121
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-A8CF3A5021
Generated	2026-08-06

Product Overview

Star-delta switches, Contacts: 10, 32 A, front plate: 0-Y-D, 60 °, maintained, rear mounting, SOND 28
Switch Star-Triangle; 10-pole; 32; Plate indicator: 0 -, And-D; 60 °; Interlocking; Installation bottom panel; SOND 28
Eaton Moeller® series T3 Star-delta switches, T3, 32 A, rear mounting, 5 contact unit(s), Contacts: 10, 60 °, maintained, With 0 (Off) position, 0-Y-D, SOND 28, Design number 15899
Star-delta switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 28, Contacts: 10, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Star-delta switch Catalog Number 004121 Model Code T3-5-15899/Z EAN 4015080041214 Product Length/Depth 167 mm Product Height 54 mm Product Width 61 mm Product Weight 0.29 kg

Certifications CE

IEC/EN 60204

VDE 0660

CSA

CSA File No.: 012528

UL Category Control No.: NLRV

CSA Class No.: 3211-05

CSA-C22.2 No. 60947-4-1-14

UL

UL File No.: E36332

CSA-C22.2 No. 94

IEC/EN 60947-3

UL 60947-4-1

IEC/EN 60947 Catalog Notes Rated Short-time Withstand Current (I_{cs}) for a time of 1 second

ETIM for 004121 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

18.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Housing....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-15899/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.