

INDUSTRIAL COMPONENT DATA

T3-6-15893/E 004342 Y7-4342 EATON ELECTRIC Star-delta switches, Contacts: 11, 32 A, front plate: B 0-Y-D, 60..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-6-15893/E



Manufacturer	EATON - MOELLER
MPN / Reference	T3-6-15893/E
Catalog number	Y7-4342
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-06FB3173D7
Generated	2026-08-04

Product Overview

Star-delta switches, Contacts: 11, 32 A, front plate: B>0-Y-D, 60 °, momentary/maintained, flush mounting, SOND 29 Switch Star-Triangle; 11-pole; 32; Plate indicator: B>0-And-D; 60 °; - Return/Latching; flush Mount; SOND 29 Eaton Moeller® series T3 Star-delta switches, T3, 32 A, flush mounting, 6 contact unit(s), Contacts: 11, 60 °, momentary/maintained, With 0 (Off) position, With spring-return to 0, B>0-Y-D, SOND 29, Design number 15893 Star-delta switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 29, Contacts: 11, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 60 °, Switching performance: momentary/maintained, With 0 (Off) position, With spring-return to 0, front plate: B>0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: Iu = 32 A, 6 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Star-delta switch Catalog Number 004342 Model Code T3-6-15893/E EAN 4015080043423 Product Length/Depth 137 mm Product Height 54 mm Product Width 61 mm Product Weight 0.332 kg

Certifications VDE 0660

CSA-C22.2 No. 60947-4-1-14

UL

UL 60947-4-1

CSA

IEC/EN 60204

UL File No.: E36332

CSA File No.: 012528

CSA-C22.2 No. 94

IEC/EN 60947-3

UL Category Control No.: NLRV

CE

IEC/EN 60947

CSA Class No.: 3211-05 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 004342 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Star-delta switch

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

Yes

Rated permanent current I_u (EF001389)

32 A

Rated operation current I_e at AC-3, 400 V (EF001392)

23.7 A

Rated operation power at AC-3, 400 V (EF001364)

18.5 kW

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

12

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-6-15893/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.