

INDUSTRIAL COMPONENT DATA

T3-5-25/Z 004139 Y7-4139 EATON ELECTRIC Star-delta switches, Contacts: 9, 32 A, front plate: 0-Y-D, 60 °, ma..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-25/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-25/Z
Catalog number	Y7-4139
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-75509FDDCF
Generated	2026-08-06

Product Overview

Star-delta switches, Contacts: 9, 32 A, front plate: 0-Y-D, 60 °, maintained, rear mounting, SOND 29

Switch Star-Triangle; 9-pole; 32; Plate indicator: 0 -, And-D; 60 °; Interlocking; Installation bottom panel; SOND 29

Star-delta switches, T3, 32 A, rear mounting, 5 contact unit(s), Contacts: 9, 60 °, maintained, With 0 (Off) position, 0-Y-D, SOND 29, Design number 25

Star-delta switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 29, Contacts: 9, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

Star-delta switches, T3, 32 A, rear mounting, 5 contact unit(s), Contacts: 9, 60 °, maintained, With 0 (Off) position, 0-Y-D, SOND 29, Design number 25Star-delta switch, Product range: Control switches, Part group reference: T3, with black thumb grip and front plate, Notes: SOND 29, Contacts: 9, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-Y-D, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 15 kW, Rated uninterrupted current: I_u = 32 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

General specificationsProduct nameEaton Moeller® series T3 Star-delta switchPart

no.T3-5-25/ZEAN4015080041399Product Length/Depth167 millimetreProduct height54 millimetreProduct width61 millimetreProduct weight0.29 kilogramCertificationsCSA

UL 60947-4-1

IEC/EN 60947

UL File No.: E36332

IEC/EN 60204

CSA Class No.: 3211-05

VDE 0660

CE

UL

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60947-3

CSA File No.: 012528

UL Category Control No.: NLRV

CSA-C22.2 No. 94

CSA

ULProduct TradenameT3Product TypeStar-delta switchProduct Sub TypeNoneCatalog NotesRated Short-time Withstand Current (Icw) for a time of 1 secondFeatures & FunctionsEnclosure materialPlasticFitted with:Black thumb grip and front plate

0 (off) positionInscription0-Y-DNumber of poles3General informationDegree of protectionIP65

NEMA 1

NEMA 12Degree of protection (front side)IP...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-25/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.