

INDUSTRIAL COMPONENT DATA

STD32 EATON ELECTRIC Eaton Basic Rack PDU, 0U, 24U, C20 input, 4 kW, 16A, 200-240V, Outlets: (20) C13/(4) C1..

Brand: EATON - MOELLER | Manufacturer Part Number: STD32



Manufacturer	EATON - MOELLER
MPN / Reference	STD32
Catalog number	10000
Category	HRC fuse
Minimum order	20 Pcs
Document ID	EO-B302FFF344
Generated	2026-08-05

Product Overview

32AMP 240V AC INDUSTRIAL CARTON QTY. 20

Fuse-link, LV, 32 A, AC 240 V, BS88, 12 x 47 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 32 A, AC 240 V, BS88, 12 x 47 mm, gL/gG, BS, offset bolted tags (slotted), street lighting cut-outs, BS88-1, Breaking Capacity 33 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories**

Additional Product Information

General specifications

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number STD32 EAN 5027590512633

UPC 051712844680 Product Length/Depth 47 mm Product Height 12 mm Product Width 13 mm Product Weight 11 g

Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 32 A Voltage rating 240 V Voltage type AC Breaking capacity 33 kA Class Class gG/gL Product specifications

Fuse type STD Fitted with: Offset bolted tags Construction BS88

ETIM for STD32 Circuit breakers and fuses (EC004556)

Feature Name

Feature Value

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

240 V

Rated current (EF000227)

32 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

33 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

2.4 W

Mounting holes (EF021553)

Other

Centre-to-centre distance of connections (EF021151)

35 mm

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / STD32 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.