

**INDUSTRIAL COMPONENT DATA**

# STD32 EATON ELECTRIC Eaton Basic Rack PDU, 0U, 24U, C20 input, 4 kW, 16A, 200-240V, Outlets: (20) C13/(4) C1..

Brand: EATON - MOELLER | Manufacturer Part Number: STD32



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | STD32           |
| Catalog number  | 10000           |
| Category        | HRC fuse        |
| Minimum order   | 20 Pcs          |
| Document ID     | EO-B302FFF344   |
| Generated       | 2026-08-06      |

## Product Overview

32AMP 240V AC INDUSTRIAL CARTON QTY. 20

Fuse-link, LV, 32 A, AC 240 V, BS88, 12 x 47 mm, gL/gG, BS

Fuse, Fuse-link, low voltage, 32 A, AC 240 V, BS88, 12 x 47 mm, gL/gG, BS, offset bolted tags (slotted), street lighting cut-outs, BS88-1, Breaking Capacity 33 kA

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **EATON - MOELLER > Bussmann Series Low Voltage fuses and accessories**

## Additional Product Information

**General specifications**

Product Name Eaton Bussmann series low voltage british standard fuse Catalog Number STD32 EAN 5027590512633

UPC 051712844680 Product Length/Depth 47 mm Product Height 12 mm Product Width 13 mm Product Weight 11 g

Compliances CE Marked

RoHS Compliant Certifications BS88

IEC 60269

EAC Electrical data

Amperage Rating 32 A Voltage rating 240 V Voltage type AC Breaking capacity 33 kA Class Class gG/gL Product specifications

Fuse type STD Fitted with: Offset bolted tags Construction BS88

ETIM for STD32 Circuit breakers and fuses (EC004556)

Feature Name

**Feature Value**

Fuse system according to IEC 60269 (EF017676)

Other

Fuse construction type according to IEC 60269 (EF015865)

Other

Type of current (EF000143)

AC

Rated voltage AC (EF007682)

240 V

Rated current (EF000227)

32 A

Utilization category according to IEC 60269 (EF002572)

gG (cable protection/equipment protection)

Breaking capacity (EF005617)

33 kA

Colour code (EF000931)

None

Type of fuse status indicator (EF004473)

None

Power loss at rated current (EF012389)

2.4 W

Mounting holes (EF021553)

Other

Centre-to-centre distance of connections (EF021151)

35 mm

**REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW**

Send EATON - MOELLER / STD32 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.