

## INDUSTRIAL COMPONENT DATA

# T0-3-8243/XZ 013449 Y7-13449 EATON ELECTRIC Contacts: 5, 20 A, 45 °, rear mounting, Basic switch

Brand: EATON - MOELLER | Manufacturer Part Number: T0-3-8243/XZ



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T0-3-8243/XZ    |
| Catalog number  | Y7-13449        |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-AE6D3EE527   |
| Generated       | 2026-08-04      |

## Product Overview

Contacts: 5, 20 A, 45 °, rear mounting, Basic switch

Step switch 5 poles 20 A Indicator plate: 0-5 45°5

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER &gt; Disconnectors and Cam Switches

## Additional Product Information

Contacts: 5, 20 A, 45 °, rear mounting, Basic switchControl switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, Contacts: 5, Design: rear mounting, Basic switch, Switching angle: 45 °, 3 contact unit(s), Rated uninterrupted current: Iu= 20 A  
Delivery program

Product rangeControl switchesPart group referenceT0Contacts5Designrear mounting

Basic switchContact sequenceSwitching angle45 °Design number8243Front plate no.Motor rating AC-23A, 50 - 60 Hz  
[P]400 V [P]5.5 kWRated uninterrupted current [Iu]20 ANote on rated uninterrupted current IuRated uninterrupted current Iuis specified for max. cross-section.Number of contact units3 contact unit(s)Technical data

GeneralStandardsIEC/EN 60947, VDE 0660, IEC/EN 60204

Switch-disconnector according to IEC/EN 60947-3Climatic proofingDamp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30Ambient temperatureOpen-25 - +50 °CAmbient temperatureEnclosed-25 - +40

°COvervoltage category/pollution degreeIII/3Rated impulse withstand voltage [Uimp]6000 V ACMechanical shock

resistance15 gMounting positionAs requiredContactsElectrical characteristicsRated operational voltage [Ue]690 V

ACElectrical characteristicsRated uninterrupted current [Iu]20 AElectrical characteristicsNote on rated uninterrupted current

!uRated uninterrupted current Iuis specified for max. cross-section.Load rating with intermittent operation, class...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-3-8243/XZ with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.