

INDUSTRIAL COMPONENT DATA

T0-2-8241/Z 062581 Y7-62581 EATON ELECTRIC Step switches, Contacts: 3, 20 A, front plate: 0-3, 45 °, 3 steps..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-8241/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-8241/Z
Catalog number	Y7-62581
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-1EB4ADAD5D
Generated	2026-08-06

Product Overview

Step switches, Contacts: 3, 20 A, front plate: 0-3, 45 °, 3 steps, 45°, maintained, rear mounting

Step switch; 3 poles; 20 A; Indicator plate: 0-3; 45 °;

Eaton Moeller® series T0 Step switches, T0, 20 A, rear mounting, 2 contact unit(s), Contacts: 3, 45 °, maintained, With 0 (Off) position, 0-3, Design number 8241

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 3, Number of steps: 3 steps, 45°, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A, front plate: 0-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 062581 Model Code T0-2-8241/Z EAN

4015080625810 Product Length/Depth 128 mm Product Height 48 mm Product Width 48 mm Product Weight 0.134 kg

Certifications CSA-C22.2 No. 60947-4-1-14

CSA-C22.2 No. 94

UL Category Control No.: NLRV

CSA File No.: 012528

IEC/EN 60204

UL 60947-4-1

UL

UL File No.: E36332

CSA

CSA Class No.: 3211-05

IEC/EN 60947

IEC/EN 60947-3

CE

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cn}) for a time of 1 second

ETIM for 062581 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_n (EF001389)

20 A

Number of switch positions (EF000231)

4

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-8241/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.