

INDUSTRIAL COMPONENT DATA

T0-5-8247/IVS 052467 Y7-52467 EATON ELECTRIC Step switches, Contacts: 9, 20 A, front plate: 0-9, 30 °, maint..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-8247/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-8247/IVS
Catalog number	Y7-52467
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-8171B6C76F
Generated	2026-08-05

Product Overview

Step switches, Contacts: 9, 20 A, front plate: 0-9, 30 °, maintained, service distribution board mounting

Step switch 9 poles 20 A Indicator plate: 0-9 30°

Eaton Moeller® series T0 Step switches, T0, 20 A, service distribution board mounting, 5 contact unit(s), Contacts: 9, 30 °, maintained, With 0 (Off) position, 0-9, Design number 8247

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 9, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 30 °, Switching performance: maintained, With 0 (Off) position, 5 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 0-9

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 052467 Model Code T0-5-8247/IVS EAN 4015080524670 Product Length/Depth 120 mm Product Height 55 mm Product Width 54 mm Product Weight 0.205 kg

Certifications CSA-C22.2 No. 94

IEC/EN 60204

UL

UL Category Control No.: NLRV

IEC/EN 60947-3

CSA File No.: 012528

CE

CSA

UL 60947-4-1

CSA-C22.2 No. 60947-4-1-14

UL File No.: E36332

CSA Class No.: 3211-05

IEC/EN 60947

VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 052467 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

1

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

20 A

Number of switch positions (EF000231)

10

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

4

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-8247/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.