

INDUSTRIAL COMPONENT DATA

T3-2-8231/EZ 018449 Y7-18449 EATON ELECTRIC Step switches, Contacts: 4, 32 A, front plate: 1-4,, 4 steps, 60..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-2-8231/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-2-8231/EZ
Catalog number	Y7-18449
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-19FEA1C795
Generated	2026-08-06

Product Overview

Step switches, Contacts: 4, 32 A, front plate: 1-4,, 4 steps, 60° maintained, centre mounting

Step Switch 4 Pole 32 A Indicator Plate: 1-4 45°

Eaton Moeller® series T3 Step switches, T3, 32 A, centre mounting, 2 contact unit(s), Contacts: 4, 60 °, maintained, Without 0 (Off) position, 1-4, Design number 8231

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 4, Number of steps: 4 steps, 60°, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 60 °, Switching performance: maintained, Without 0 (Off) position, 2 contact unit(s), Rated uninterrupted current: Iu= 32 A, front plate: 1-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Step switch Catalog Number 018449 Model Code T3-2-8231/EZ EAN

4015080184492 Product Length/Depth 113 mm Product Height 54 mm Product Width 61 mm Product Weight 0.179 kg

Certifications CSA-C22.2 No. 94

CSA-C22.2 No. 60947-4-1-14

UL

VDE 0660

IEC/EN 60204

CSA File No.: 012528

UL 60947-4-1

UL File No.: E36332

IEC/EN 60947

IEC/EN 60947-3

CSA

CE

CSA Class No.: 3211-05

UL Category Control No.: NLRV Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 018449 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

32 A

Number of switch positions (EF000231)

4

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-2-8231/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.