

## INDUSTRIAL COMPONENT DATA

# T5B-4-8244/E 092096 Y7-92096 EATON ELECTRIC Step switches, Contacts: 6, 63 A, front plate: 0-6, 45 °, mainta..

Brand: EATON - MOELLER | Manufacturer Part Number: T5B-4-8244/E



|                 |                 |
|-----------------|-----------------|
| Manufacturer    | EATON - MOELLER |
| MPN / Reference | T5B-4-8244/E    |
| Catalog number  | Y7-92096        |
| Category        | Control switch  |
| Minimum order   | 1 Pcs           |
| Document ID     | EO-78634FB69B   |
| Generated       | 2026-08-04      |

## Product Overview

Step switches, Contacts: 6, 63 A, front plate: 0-6, 45 °, maintained, flush mounting

Step switch 6 poles 63 A Indicator plate: 0-6 45°

Eaton Moeller® series T5B Step switches, T5B, 63 A, flush mounting, 4 contact unit(s), Contacts: 6, 45 °, maintained, With 0 (Off) position, 0-6, Design number 8244

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T5B, with black thumb grip and front plate, Contacts: 6, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, 4 contact unit(s), Rated uninterrupted current: I<sub>u</sub>= 63 A, front plate: 0-6

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

## Additional Product Information

## General specifications

Product Name Eaton Moeller® series T5B Step switch Catalog Number 092096 Model Code T5B-4-8244/E EAN 4015080920960 Product Length/Depth 141 mm Product Height 88 mm Product Width 88 mm Product Weight 0.725 kg

Certifications UL

UL File No.: E36332

CSA Class No.: 3211-07

UL Category Control No.: NLRV

VDE 0660

CE  
CSA  
CSA File No.: 012528  
CSA-C22.2 No. 60947-4-1-14  
IEC/EN 60947-3  
UL 60947-4-1  
CSA-C22.2 No. 94  
IEC/EN 60947  
IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (I<sub>cw</sub>) for a time of 1 second  
ETIM for 092096 Low-voltage industrial controls and switchgear (EC002611)  
Feature Name  
Feature Value  
Type of switch (EF003496)  
Level switch  
Number of poles (EF001391)  
1  
Max. rated operation voltage U<sub>e</sub> AC (EF007355)  
690 V  
Rated permanent current I<sub>u</sub> (EF001389)  
63 A  
Number of switch positions (EF000231)  
7  
With zero (off) position (EF001416)  
Yes  
With retraction in 0-position (EF002428)  
No  
Device construction (EF008240)  
Built-in device  
Width in number of modular spacings (EF002950)  
0  
Suitable for floor mounting (EF007243)  
No  
Suitable for front mounting (EF007246)  
Yes  
Suitable for distribution board installation (EF007262)  
No  
Suitable for intermediate mounting (EF007264)  
No  
Complete device in housing (EF007317)  
No  
Type of control element (EF006976)  
Toggle  
Front shield size (EF007176)  
88x88 mm  
Degree of protection (IP), front side (EF003118)  
IP65  
Degree of protection (NEMA), front side (EF011961)

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T5B-4-8244/E with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.