

INDUSTRIAL COMPONENT DATA

T0-6-8271/E 015124 Y7-15124 EATON ELECTRIC Step switches, Contacts: 12, 20 A, front plate: 1-4, 45 °, 4 step..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-8271/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-6-8271/E
Catalog number	Y7-15124
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-1180604152
Generated	2026-08-04

Product Overview

Step switches, Contacts: 12, 20 A, front plate: 1-4, 45 °, 4 steps, 45°, maintained, flush mounting

Step switch 12 poles 20 A Indicator plate: 1-4 45°

Eaton Moeller® series T0 Step switches, T0, 20 A, flush mounting, 6 contact unit(s), Contacts: 12, 45 °, maintained, Without 0 (Off) position, 1-4, Design number 8271

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 12, Number of steps: 4 steps, 45°, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 45 °, Switching performance: maintained, Without 0 (Off) position, 6 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: 1-4

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 015124 Model Code T0-6-8271/E EAN 4015080151241 Product Length/Depth 124 mm Product Height 48 mm Product Width 48 mm Product Weight 0.16 kg

Certifications IEC/EN 60947

IEC/EN 60947-3

CE

CSA-C22.2 No. 94

CSA

UL Category Control No.: NLRV

CSA Class No.: 3211-05

CSA-C22.2 No. 60947-4-1-14

UL 60947-4-1

UL

IEC/EN 60204

VDE 0660

UL File No.: E36332

CSA File No.: 012528 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 015124 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

3

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

20 A

Number of switch positions (EF000231)

4

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-8271/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.