

INDUSTRIAL COMPONENT DATA

T3-5-8281/Z 064237 Y7-64237 EATON ELECTRIC Step switches, Contacts: 9, 32 A, front plate: 0-3, 45 °, maintai..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-8281/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-8281/Z
Catalog number	Y7-64237
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-D7AEB9785C
Generated	2026-08-05

Product Overview

Step switches, Contacts: 9, 32 A, front plate: 0-3, 45 °, maintained, rear mounting

Step switch 9 poles 32 A Indicator plate: 0-3 45°

Eaton Moeller® series T3 Step switches, T3, 32 A, rear mounting, 5 contact unit(s), Contacts: 9, 45 °, maintained, With 0 (Off) position, 0-3, Design number 8281

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 9, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, 5 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: 0-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Step switch Catalog Number 064237 Model Code T3-5-8281/Z EAN 4015080642374 Product Length/Depth 167 mm Product Height 54 mm Product Width 61 mm Product Weight 0.29 kg

Certifications IEC/EN 60204

UL File No.: E36332

IEC/EN 60947

CE

CSA-C22.2 No. 60947-4-1-14

CSA
IEC/EN 60947-3
UL
UL Category Control No.: NLRV
CSA Class No.: 3211-05
VDE 0660
UL 60947-4-1
CSA File No.: 012528
CSA-C22.2 No. 94 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 064237 Low-voltage industrial controls and switchgear (EC002611)
Feature Name
Feature Value
Type of switch (EF003496)
Level switch
Number of poles (EF001391)
3
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated permanent current Iu (EF001389)
32 A
Number of switch positions (EF000231)
4
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Device construction (EF008240)
Built-in device
Width in number of modular spacings (EF002950)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
Yes
Complete device in housing (EF007317)
No
Type of control element (EF006976)
Toggle
Front shield size (EF007176)
48x48 mm
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-8281/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.