

INDUSTRIAL COMPONENT DATA

T0-2-96/IVS 012244 Y7-12244 EATON ELECTRIC step switch for heating, Contacts: 3, 20 A, front plate: 0-3, 60 ..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-96/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-96/IVS
Catalog number	Y7-12244
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-E25D7E3930
Generated	2026-08-03

Product Overview

step switch for heating, Contacts: 3, 20 A, front plate: 0-3, 60 °, maintained, service distribution board mounting
Switch steps for heating; 3-pole; 20a; rating Plate: 0-3; 60 °; Interlock; Mounting in control cabinet
Eaton Moeller® series T0 step switch for heating, T0, 20 A, service distribution board mounting, 2 contact unit(s), Contacts: 3, 60 °, maintained, With 0 (Off) position, 0-3, Design number 96
Step switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 3, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 60 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-3, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 012244 Model Code T0-2-96/IVS EAN 4015080122449 Product Length/Depth 92 mm Product Height 55 mm Product Width 54 mm Product Weight 0.12 kg

Certifications CE

VDE 0660

CSA-C22.2 No. 94

UL 60947-4-1

CSA File No.: 012528

IEC/EN 60947

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

UL Category Control No.: NLRV

CSA Class No.: 3211-05

IEC/EN 60947-3

CSA

UL File No.: E36332

UL Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 012244 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

On/Off switch

Number of poles (EF001391)

1

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current I_u (EF001389)

20 A

Rated operation current I_e at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF0015...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-96/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.