

INDUSTRIAL COMPONENT DATA

T0-2-8312/I1 222620 Y7-222620 EATON ELECTRIC Step switches, Contacts: 4, 20 A, front plate: 0-2, 45 °, maint..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-8312/I1



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-8312/I1
Catalog number	Y7-222620
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-529504B6ED
Generated	2026-08-05

Product Overview

Step switches, Contacts: 4, 20 A, front plate: 0-2, 45 °, maintained, surface mounting

T0-2-8312/I1

Eaton Moeller® series T0 Step switches, T0, 20 A, surface mounting, 2 contact unit(s), Contacts: 4, 45 °, maintained, With 0 (Off) position, 0-2, Design number 8312

Step switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 4, Degree of Protection: IP65, Design: surface mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-2, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 2 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 222620 Model Code T0-2-8312/I1 EAN

4015082226206 Product Length/Depth 137 mm Product Height 102 mm Product Width 80 mm Product Weight 0.264 kg

Certifications VDE 0660

IEC/EN 60947

IEC/EN 60947-3

IEC/EN 60204 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 222620 Low-voltage industrial controls and switchgear (EC001105)

Feature Name
Feature Value
Model (EF000010)
Reverser
Number of poles (EF001391)
2
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Rated permanent current I_u (EF001389)
20 A
Rated operation current I_e at AC-3, 400 V (EF001392)
11.5 A
Rated operation power at AC-3, 400 V (EF001364)
4 kW
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)
12
Number of auxiliary contacts as normally closed contact (EF001377)
0
Number of auxiliary contacts as normally open contact (EF001376)
0
Number of auxiliary contacts as change-over contact (EF003531)
0
Suitable for floor mounting (EF007243)
Yes
Suitable for front mounting (EF007246)
No
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)
Yes
Housing material (EF001596)
Plastic
Type of control element (EF006976)
Short thumb-grip
Type of electrical connection of main circuit (EF006819)
Screw connection

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-8312/I1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.