

INDUSTRIAL COMPONENT DATA

T3-5-15133/EZ 004035 Y7-4035 EATON ELECTRIC Step switches, Contacts: 10, 32 A, front plate: 0-5, 45 °, maint..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-15133/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-15133/EZ
Catalog number	Y7-4035
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-EC7658447A
Generated	2026-08-03

Product Overview

Step switches, Contacts: 10, 32 A, front plate: 0-5, 45 °, maintained, centre mounting
Switch steps; 10-pole; 32; Plate indicator: 0-5; 45 °; Interlock; recessed Mounting with central fixing
Eaton Moeller® series T3 Step switches, T3, 32 A, centre mounting, 5 contact unit(s), Contacts: 10, 45 °, maintained, With 0 (Off) position, 0-5, Design number 15133
Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL,
Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate,
Contacts: 10, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 45 °, Switching performance:
maintained, With 0 (Off) position, 5 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: 0-5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Step switch Catalog Number 004035 Model Code T3-5-15133/EZ EAN 4015080040354 Product Length/Depth 147 mm Product Height 54 mm Product Width 61 mm Product Weight 0.32 kg
Certifications CSA-C22.2 No. 60947-4-1-14
IEC/EN 60204
CSA-C22.2 No. 94
CSA File No.: 012528
CSA Class No.: 3211-05

UL
UL File No.: E36332
UL 60947-4-1
CSA
IEC/EN 60947
IEC/EN 60947-3
UL Category Control No.: NLRV
VDE 0660
CE Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second
ETIM for 004035 Low-voltage industrial controls and switchgear (EC002611)
Feature Name
Feature Value
Type of switch (EF003496)
Level switch
Number of poles (EF001391)
2
Max. rated operation voltage Ue AC (EF007355)
690 V
Rated permanent current Iu (EF001389)
32 A
Number of switch positions (EF000231)
6
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
No
Device construction (EF008240)
Built-in device
Width in number of modular spacings (EF002950)
0
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)
No
Type of control element (EF006976)
Toggle
Front shield size (EF007176)
48x48 mm
Degree of protection (IP), front side (EF003118)
IP65
Degree of protection (NEMA), front side (EF011961)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-15133/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.