


INDUSTRIAL COMPONENT DATA

T3-5-15139/Z 004041 Y7-4041 EATON ELECTRIC Step switches, Contacts: 10, 32 A, front plate: 1-5, 45 °, mainta..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-5-15139/Z



Manufacturer	EATON - MOELLER
MPN / Reference	T3-5-15139/Z
Catalog number	Y7-4041
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-FFD71EA696
Generated	2026-08-03

Product Overview

Step switches, Contacts: 10, 32 A, front plate: 1-5, 45 °, maintained, rear mounting

Switch steps; 10-pole; 32; rating Plate: 1-5; 45 °; Interlock; Mounting bottom panel

Eaton Moeller® series T3 Step switches, T3, 32 A, rear mounting, 5 contact unit(s), Contacts: 10, 45 °, maintained, Without 0 (Off) position, 1-5, Design number 15139

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 10, Degree of Protection: Front IP65, Design: rear mounting, Switching angle: 45 °, Switching performance: maintained, Without 0 (Off) position, 5 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: 1-5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Step switch Catalog Number 004041 Model Code T3-5-15139/Z EAN

4015080040415 Product Length/Depth 167 mm Product Height 54 mm Product Width 61 mm Product Weight 0.326 kg

Certifications CE

IEC/EN 60947-3

CSA-C22.2 No. 60947-4-1-14

UL

VDE 0660

UL 60947-4-1

IEC/EN 60947

UL Category Control No.: NLRV

CSA Class No.: 3211-05

CSA File No.: 012528

IEC/EN 60204

CSA-C22.2 No. 94

CSA

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 004041 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

2

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

32 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

Yes

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-5-15139/Z with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.