

INDUSTRIAL COMPONENT DATA

T3-8-15152/EZ 005651 Y7-5651 EATON ELECTRIC Step switches, Contacts: 15, 32 A, front plate: 1-5, 45 °, maint..

Brand: EATON - MOELLER | Manufacturer Part Number: T3-8-15152/EZ



Manufacturer	EATON - MOELLER
MPN / Reference	T3-8-15152/EZ
Catalog number	Y7-5651
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-942DB58BC1
Generated	2026-08-02

Product Overview

Step switches, Contacts: 15, 32 A, front plate: 1-5, 45 °, maintained, centre mounting

Switch steps; 15-pole; 32; rating Plate: 1-5; 45 °; Interlock; recessed Mounting with central fixing

Eaton Moeller® series T3 Step switches, T3, 32 A, centre mounting, 8 contact unit(s), Contacts: 15, 45 °, maintained, Without 0 (Off) position, 1-5, Design number 15152

Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T3, with black thumb grip and front plate, Contacts: 15, Degree of Protection: Front IP65, Design: center mounting, Switching angle: 45 °, Switching performance: maintained, Without 0 (Off) position, 8 contact unit(s), Rated uninterrupted current: I_u= 32 A, front plate: 1-5

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path EATON - MOELLER > Disconnectors and Cam Switches

Additional Product Information

General specifications

Product Name Eaton Moeller® series T3 Step switch Catalog Number 005651 Model Code T3-8-15152/EZ EAN 4015080056515 Product Length/Depth 182 mm Product Height 54 mm Product Width 61 mm Product Weight 0.412 kg

Certifications CE

IEC/EN 60947-3

CSA Class No.: 3211-05

CSA File No.: 012528

UL

UL File No.: E36332

VDE 0660

IEC/EN 60947

CSA-C22.2 No. 94

IEC/EN 60204

CSA

CSA-C22.2 No. 60947-4-1-14

UL Category Control No.: NLRV

UL 60947-4-1 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second

ETIM for 005651 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

3

Max. rated operation voltage U_e AC (EF007355)

690 V

Rated permanent current I_u (EF001389)

32 A

Number of switch positions (EF000231)

5

With zero (off) position (EF001416)

No

With retraction in 0-position (EF002428)

No

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

No

Suitable for front mounting (EF007246)

Yes

Suitable for distribution board installation (EF007262)

No

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Type of control element (EF006976)

Toggle

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T3-8-15152/EZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.