

INDUSTRIAL COMPONENT DATA

T0-2-15003/E 011159 Y7-11159 EATON ELECTRIC Step switches, Contacts: 3, 20 A, front plate: 1-3, 45 °, Uninte..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-2-15003/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-2-15003/E
Catalog number	Y7-11159
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-79E63964F4
Generated	2026-08-05

Product Overview

Step switches, Contacts: 3, 20 A, front plate: 1-3, 45 °, Uninterruptible, maintained, flush mounting
Switch steps; 3-pole; 20a; rating Plate: 1-3; 45 °; Uninterruptible power supply; Interlocking; flush Mount
Eaton Moeller® series T0 Step switches, T0, 20 A, flush mounting, 2 contact unit(s), Contacts: 3, 45 °, maintained, Without 0 (Off) position, 1-3, Design number 15003
Step switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL,
Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate,
Contacts: 3, Contact behavior: Uninterruptible, Degree of Protection: Front IP65, Design: flush mounting, Switching angle:
45 °, Switching performance: maintained, Without 0 (Off) position, 2 contact unit(s), Rated uninterrupted current: I_u= 20 A,
front plate: 1-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 011159 Model Code T0-2-15003/E EAN 4015080111597 Product Length/Depth 86 mm Product Height 48 mm Product Width 48 mm Product Weight 0.108 kg
Certifications CSA-C22.2 No. 94
IEC/EN 60947-3
CSA
CSA File No.: 012528

CSA-C22.2 No. 60947-4-1-14

VDE 0660

CSA Class No.: 3211-05

UL 60947-4-1

IEC/EN 60947

UL

UL Category Control No.: NLRV

CE

IEC/EN 60204

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 011159 Low-voltage industrial controls and switchgear (EC002611)

Feature Name

Feature Value

Type of switch (EF003496)

Level switch

Number of poles (EF001391)

1

Max. rated operation voltage Ue AC (EF007355)

690 V

Rated permanent current Iu (EF001389)

20 A

Number of switch positions (EF000231)

3

With zero (off) position (EF001416)

false

With retraction in 0-position (EF002428)

false

Device construction (EF008240)

Built-in device

Width in number of modular spacings (EF002950)

0

Suitable for floor mounting (EF007243)

false

Suitable for front mounting (EF007246)

true

Suitable for distribution board installation (EF007262)

false

Suitable for intermediate mounting (EF007264)

false

Complete device in housing (EF007317)

false

Type of control element (EF006976)

Wing knob

Front shield size (EF007176)

48x48 mm

Degree of protection (IP), front side (EF003118)

IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-2-15003/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.