

INDUSTRIAL COMPONENT DATA

T0-5-8315/IVS 014949 Y7-14949 EATON ELECTRIC Step switches, Contacts: 9, 20 A, front plate: 0-3, 45 °, maint..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-5-8315/IVS



Manufacturer	EATON - MOELLER
MPN / Reference	T0-5-8315/IVS
Catalog number	Y7-14949
Category	Off-load switch
Minimum order	1 Pcs
Document ID	EO-7209B15F60
Generated	2026-08-03

Product Overview

Step switches, Contacts: 9, 20 A, front plate: 0-3, 45 °, maintained, service distribution board mounting

Step switch 9 poles 20 A Indicator plate: 0-3 45°

Eaton Moeller® series T0 Step switches, T0, 20 A, service distribution board mounting, 5 contact unit(s), Contacts: 9, 45 °, maintained, With 0 (Off) position, 0-3, Design number 8315

Step switch, Product range: Control switches, Part group reference: T0, with black thumb grip and front plate, Contacts: 9, Degree of Protection: Front IP30, Design: service distribution board mounting, Switching angle: 45 °, Switching performance: maintained, With 0 (Off) position, front plate: 0-3, Motor rating AC-23A, 50 - 60 Hz 400 V: P = 5.5 kW, Rated uninterrupted current: Iu = 20 A, 5 contact unit(s), Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Disconnectors and Cam Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Step switch Catalog Number 014949 Model Code T0-5-8315/IVS EAN

4015080149491 Product Length/Depth 120 mm Product Height 55 mm Product Width 54 mm Product Weight 0.205 kg

Certifications UL

UL Category Control No.: NLRV

VDE 0660

CSA

CE

CSA-C22.2 No. 60947-4-1-14

IEC/EN 60204

IEC/EN 60947-3

CSA File No.: 012528

CSA Class No.: 3211-05

IEC/EN 60947

UL 60947-4-1

CSA-C22.2 No. 94

UL File No.: E36332 Catalog Notes Rated Short-time Withstand Current (Icw) for a time of 1 second

ETIM for 014949 Low-voltage industrial controls and switchgear (EC001105)

Feature Name

Feature Value

Model (EF000010)

Reverser

Number of poles (EF001391)

3

With zero (off) position (EF001416)

Yes

With retraction in 0-position (EF002428)

No

Rated permanent current Iu (EF001389)

20 A

Rated operation current Ie at AC-3, 400 V (EF001392)

11.5 A

Rated operation power at AC-3, 400 V (EF001364)

4 kW

Degree of protection (IP), front side (EF003118)

IP30

Degree of protection (NEMA), front side (EF011961)

2

Number of auxiliary contacts as normally closed contact (EF001377)

0

Number of auxiliary contacts as normally open contact (EF001376)

0

Number of auxiliary contacts as change-over contact (EF003531)

0

Suitable for floor mounting (EF007243)

Yes

Suitable for front mounting (EF007246)

No

Suitable for distribution board installation (EF007262)

Yes

Suitable for intermediate mounting (EF007264)

No

Complete device in housing (EF007317)

No

Housing material (EF00159...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-5-8315/IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.