

INDUSTRIAL COMPONENT DATA

T0-6-8155/E 015696 Y7-15696 EATON ELECTRIC Universal control switches, Contacts: 12, 20 A, front plate: Höhe..

Brand: EATON - MOELLER | Manufacturer Part Number: T0-6-8155/E



Manufacturer	EATON - MOELLER
MPN / Reference	T0-6-8155/E
Catalog number	Y7-15696
Category	Control switch
Minimum order	1 Pcs
Document ID	EO-9DCC94DF6E
Generated	2026-08-01

Product Overview

Universal control switches, Contacts: 12, 20 A, front plate: Höher>0

Universal control switch; 12 poles; 20 A; Indicator plate:

Eaton Moeller® series T0 Universal control switches, T0, 20 A, flush mounting, 6 contact unit(s), Contacts: 12, 90 °, momentary, With 0 (Off) position, with spring-return from both directions to 0, Höher>0

Universal control switch, Product range: Control switches, Standards: IEC/EN 60947, VDE 0660, IEC/EN 60204, CSA, UL, Switch-disconnector according to IEC/EN 60947-3, Part group reference: T0, with black thumb grip and front plate, Contacts: 12, Degree of Protection: Front IP65, Design: flush mounting, Switching angle: 90 °, Switching performance: momentary, With 0 (Off) position, with spring-return from both directions to 0, 6 contact unit(s), Rated uninterrupted current: Iu= 20 A, front plate: Höher>0

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Disconnectors and Cam Switches
--------------	--

Additional Product Information

General specifications

Product Name Eaton Moeller® series T0 Universal control switch Catalog Number 015696 Model Code T0-6-8155/E EAN 4015080156963 Product Length/Depth 124 mm Product Height 48 mm Product Width 48 mm Product Weight 0.16 kg

Certifications CSA File No.: 012528

IEC/EN 60204

UL File No.: E36332

CSA

UL 60947-4-1
IEC/EN 60947-3
UL
CSA-C22.2 No. 60947-4-1-14
CSA-C22.2 No. 94
CSA Class No.: 3211-05
CE
UL Category Control No.: NLRV
IEC/EN 60947
VDE 0660 Catalog Notes Rated Short-time Withstand Current (I_{cw}) for a time of 1 second
ETIM for 015696 Low-voltage industrial controls and switchgear (EC002611)
Feature Name
Feature Value
Type of switch (EF003496)
Reverser
Number of poles (EF001391)
0
Max. rated operation voltage U_e AC (EF007355)
690 V
Rated permanent current I_u (EF001389)
20 A
Number of switch positions (EF000231)
3
With zero (off) position (EF001416)
Yes
With retraction in 0-position (EF002428)
Yes
Device construction (EF008240)
Built-in device
Width in number of modular spacings (EF002950)
0
Suitable for floor mounting (EF007243)
No
Suitable for front mounting (EF007246)
Yes
Suitable for distribution board installation (EF007262)
No
Suitable for intermediate mounting (EF007264)
No
Complete device in housing (EF007317)
No
Type of control element (EF006976)
Toggle
Front shield size (EF007176)
48x48 mm
Degree of protection (IP), front side (EF003118)
IP65

Degree of protection (NEMA), front side (EF011961)
12

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / T0-6-8155/E with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.