

INDUSTRIAL COMPONENT DATA

PKZ-SOL20 120938 Y7-120938 EATON ELECTRIC String circuit-breaker, DC current, 2p, 20A

Brand: EATON - MOELLER | Manufacturer Part Number: PKZ-SOL20



Manufacturer	EATON - MOELLER
MPN / Reference	PKZ-SOL20
Catalog number	Y7-120938
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-79CCECC746
Generated	2026-08-02

Product Overview

String circuit-breaker, DC current, 2p, 20A

PKZ-SOL20

Eaton Moeller® series PKZ-SOL String circuit-breaker, DC current, 2p, 20A

String circuit-breakers PKZ-SOL are the fuseless alternative for the protection of photovoltaic modules against short-circuit currents. With their variable tripping range, they can be optimally adjusted to the actual short-circuit current of a string. Using the optional delayed undervoltage release P-SOL-XUV, remote switching, for example, for the fire brigade is possible.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER > Solar Switches**

Additional Product Information

General specifications

Product Name Eaton Moeller® series PKZ-SOL String circuit-breaker Catalog Number 120938 Model Code PKZ-SOL20
EAN 4015081187683 Product Length/Depth 93 mm Product Height 76 mm Product Width 58 mm Product Weight 0.305 kg
Certifications IEC/EN 60947-2

TÜV-certified Features & Functions

Actuator type Turn button Design Open Features Complete device with protection unit Number of poles Two-pole General
Application Degree of protection IP00 Mounting Method Top-hat rail fixing (according to IEC/EN 60715, 35 mm)
DIN rail (top hat rail) mounting optional Overload release current setting - min 14 A Overload release current setting - max
20 A Product category String circuit-breakers
Switchgear for photovoltaic systems

Protection class 2 Suitable for DIN rail (top hat rail) mounting Climatic environmental conditions

Ambient operating temperature - min -25 °C Ambient operating temperature - max 60 °C Climatic proofing Damp heat, constant, to IEC 60068-2-78

Damp heat, cyclic, to IEC 60068-2-30 Terminal capacities

Terminal capacity (flexible with ferrule) 2 x (1 - 6) mm², ferrule to DIN 46228

1 x (1 - 6) mm², ferrule to DIN 46228 Terminal capacity (solid/stranded AWG) 18 - 14 Electrical rating

Internal resistance 12 mΩ Rated operational current (Ie) 20 A at AC-21A Rated operational voltage (Ue) - min 900 V Rated operational voltage (Ue) - max 900 V Rated uninterrupted current (Iu) 20 A Short-circuit current 9 - 15 A, Ics, Admissible short-circuit current for solar mo...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / PKZ-SOL20 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.