

INDUSTRIAL COMPONENT DATA

BPM-O-400/15-P 116657 Y7-116657 EATON ELECTRIC

Surface-mount installation distribution board with rotary lev..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-O-400/15-P



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-O-400/15-P
Catalog number	Y7-116657
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-0C0F475AB3
Generated	2026-08-06

Product Overview

Surface-mount installation distribution board with rotary lever, IP55, HxWxD=1560x400x270mm

BPM-O-400/15-P

IP55 surface-mounted service distribution board for damp locations, BPM-O-...-P, width 400 mm, outside height 1560 mm, front plate height 1450 mm, depth 270 mm, welded enclosure with door and rotary lever, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation, door can be right-hand or left-hand door, ample wiring area, open cable entry on top, prepared for F3A gland plate insert, variable interior fittings with or without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration , 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Surface-mount installation distribution board with rotary lever, IP55, HxWxD=1560x400x270mmIP55 surface-mounted service distribution board for damp locations, BPM-O-...-P, width 400 mm, outside height 1560 mm, front plate height 1450 mm, depth 270 mm, welded enclosure with door and rotary lever, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation, door can be right-hand or left-hand door, ample wiring area, open cable entry on top, prepared for F3A gland plate insert, variable interior fittings with or without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly

configuration , 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

General specificationsProduct nameEaton xEnergy Basic small distribution boardPart

no.BPM-O-400/15-PEAN4015081164028Product Length/Depth300 millimetreProduct height1590 millimetreProduct width430 millimetreProduct weight39.8 kilogramCompliancesRoHS conformProduct TradenamexEnergy BasicProduct TypeSmall distribution boardProduct Sub TypeNoneDelivery programTypeBasic deviceApplicationMoisture-proof (installation site)ColorLight gray (RAL 7035)

GrayTechnical Data - MechanicalClosure typeOtherSurface finishingWith powder....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-O-400/15-P with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.