

INDUSTRIAL COMPONENT DATA

BP-O-600/10-C 293308 0002456183 EATON ELECTRIC

Surface-mount service distribution board with three-point tur..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-O-600/10-C



Manufacturer	EATON - MOELLER
MPN / Reference	BP-O-600/10-C
Catalog number	0002456183
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-602D10FB0B
Generated	2026-08-04

Product Overview

Surface-mount service distribution board with three-point turn-lock, including DIN rails, front plate with 45-mm cutout; W = 600 mm, H = 1060

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

EL-Nummer (Norway)2456183Surface-mount service distribution board with three-point turn-lock, including DIN rails, front plate with 45-mm cutout; W = 600 mm, H = 1060Surface-mounted service distribution board with cam lock - completely assembled, IP30, gray, RAL 7035, width 600 mm, outside height 1060 mm, 144 HP, 6 rows, incl. base frame, enclosure side plates, base/roof panels and door, includes BPZ-DINR...B DIN-rail kits, includes front plates (150 mm) with device cutout (45 mm), includes top cable entry, with push-through flange, with blanking bottom panels, mounted on base frame - no MSW mounting kit, module design, earthed metal covers, completely mounted, can be grouped, ample wiring area, variable interior fittings with or without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand doorDelivery program

Mounting typeSurface mountedFeatureswith DIN-rail

Frontplate with 45mm cut-outMaterialSheet steelDoor interlockThree-point turn-lockInstallation siteIndoorDegree of ProtectionIP30Surface finishWith powder coatingWidth600 mmDepth262 mmHeight1060 mmColourlight gray (RAL 7035)Design verification as per IEC/EN 61439

Technical data for design verificationHeat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV]70 WHeat dissipation, at an ambien...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-O-600/10-C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.