

INDUSTRIAL COMPONENT DATA

BP-O-400/7 100960 0002459136 EATON ELECTRIC

Surface-mount service distribution board with three-point turn-l..

Brand: EATON - MOELLER | Manufacturer Part Number: BP-O-400/7



Manufacturer	EATON - MOELLER
MPN / Reference	BP-O-400/7
Catalog number	0002459136
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-2BF721DD1B
Generated	2026-08-05

Product Overview

Surface-mount service distribution board with three-point turn-lock, W = 400 mm, H = 760 mm

Surface-mounted service distribution board with cam lock - completely assembled, IP30, gray, RAL 7035, width 400 mm, outside height 760 mm, front plate height 650 mm, incl. base frame, enclosure side plates, base/roof panels and door, includes top cable entry, with push-through flange, with blanking bottom panels, mounted on base frame - no MSW mounting kit, module design, earthed metal covers, completely mounted, can be grouped, ample wiring area, variable interior fittings with or without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure , door can be right-hand or left-hand door

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER**

Additional Product Information

Surface-mount service distribution board with three-point turn-lock, W = 400 mm, H = 760 mm EL-Nummer (Norway) 0002459136 Surface-mounted service distribution board with cam lock - completely assembled, IP30, gray, RAL 7035, width 400 mm, outside height 760 mm, front plate height 650 mm, incl. base frame, enclosure side plates, base/roof panels and door, includes top cable entry, with push-through flange, with blanking bottom panels, mounted on base frame - no MSW mounting kit, module design, earthed metal covers, completely mounted, can be grouped, ample wiring area, variable interior fittings with or without removable mounting frame, well-structured, multilayered design for easily accessible installation: base frame - DIN-rails ... - enclosure, door can be right-hand or left-hand door [Delivery program

Mounting type Surface mounted Material Sheet steel Door interlock Three-point turn-lock Installation site Indoor Degree of Protection IP30 Surface finish With powder coating Width 400 mm Depth 262 mm Height 760 mm Colour light gray (RAL 7035) , Design verification as per IEC/EN 61439

Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Individual enclosure for wall mounting [PV] 54 W Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the enclosure, calculated as per IEC 60890 Starting enclosure for wall mounting [PV] 49 W Heat dissipa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-O-400/7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.