

INDUSTRIAL COMPONENT DATA

BP-O-830/12-IVS 111360 EATON ELECTRIC Surface mounted service distribution board

Brand: EATON - MOELLER | Manufacturer Part Number: BP-O-830/12-IVS



Manufacturer	EATON - MOELLER
MPN / Reference	BP-O-830/12-IVS
Catalog number	111360
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-86285C979A
Generated	2026-08-02

Product Overview

Surface mounted service distribution board

Service distribution boards IVS are used for power distribution and measurement purposes in electrical systems for household electrical systems and in comparative systems such as residential buildings, schools, administration centers, offices and similar buildings.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Delivery programme Product range Service distribution board IVS

Basic function Wall-mounting distribution system

Single unit/Complete unit Complete housing

Degree of Protection IP30 (only with door)

Description Profi Plus basic enclosures

Module design, can be dismantled completely

Exchangeable door hinges

Material Sheet steel

Surface finish Polyester powder coating

Phosphated

RAL 7035, light grey

Colour RAL 7035, light grey

Information about equipment supplied including base frame, side panels, bottom/top panels and door

Including support frame for the IVS mounting units

including insulating surround and mounted insulated support bracket

including cable entry at top, with push-through flange

Width mm 830

Height mm 1260

Depth mm 262

Technical data General

Standards EN 60439-1/3

IEC 62208

Protection class 1

Degree of Protection IP30 (only with door)

Power loss

Max. admissible heat dissipation, ambient air temperature +35 °C W 232

Weight kg 45.5

Material characteristics

Material Sheet steel

Surface treatment Painting, phosphated and polyester powder coating

Surface finish Polyester powder coating

Phosphated

RAL 7035, light grey

Colour RAL 7035, light grey

Material characteristics

Type Door Doors with covered hinges

Can be removed from 90°

door opening angle 167° (single mounting)

60° (combination mounting)

Door interlock Hinge handle with three-point turn-lock

Cylinder lock

Material properties

Mechanical

Impact resistance IK07

Cable entry Various covers allow cable entry from....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BP-O-830/12-IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.