

INDUSTRIAL COMPONENT DATA

BPM-O-830/10-IVS 111369 EATON ELECTRIC Installation distribution board, HxWxD 1060x830x262mm, IP54

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-O-830/10-IVS



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-O-830/10-IVS
Catalog number	111369
Category	Enclosure/switchgear cabinet (empty)
Minimum order	1 Pcs
Document ID	EO-792F09A307
Generated	2026-08-02

Product Overview

Installation distribution board, HxWxD=1060x830x262mm, IP54

Service distribution boards IVS are used for power distribution and measurement purposes in electrical systems for household electrical systems and in comparative systems such as residential buildings, schools, administration centers, offices and similar buildings.

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Delivery program Product range Service distribution board IVS

Basic function Wall-mounting distribution system

Single unit/Complete unit Complete housing

Degree of Protection IP55

Description Profi Plus basic enclosures

Monoblock enclosure with door and double ward key lock

The enclosure can be turned through 180° for cable entry from below.

Material Sheet steel

Surface finish Polyester powder coating

Phosphated

RAL 7035, light grey

Colour light gray (RAL 7035)

Information about equipment supplied Including mounting system for the IVS mounting units including insulating surround and mounted insulated support bracket including open cable entry at top, prepared for F3A flanges, closed at bottom

Width mm 830

Height mm 1060

Depth mm 270

Technical data General

Standards EN 60439-1/3

IEC 62208

Protection class 1

Degree of Protection IP55

Power loss

Max. admissible heat dissipation, ambient air temperature +35 °C W 196

Weight kg 44

Material characteristics

Material Sheet steel

Surface treatment Painting, phosphated and polyester powder coating

Surface finish Polyester powder coating

Phosphated

RAL 7035, light grey

Colour light gray (RAL 7035)

Material characteristics

Type Door Doors with covered hinges

Can be removed from 90°

door opening angle 100° (single mounting)

Door interlock Hinge handle with roller lever lock

Cylinder lock

Double-ward lock

Material properties

Mechanical

Impact resistance IK07

Cable entry Open cable entry, prepared for F3A flanges

Electrical

Rated operationa...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-O-830/10-IVS with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.