

INDUSTRIAL COMPONENT DATA

BPM-O-1200/15-W 111076 0002459528 EATON ELECTRIC

Surface-mounted installation distribution board with double..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-O-1200/15-W



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-O-1200/15-W
Catalog number	0002459528
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-4753FC1404
Generated	2026-08-05

Product Overview

Surface-mounted installation distribution board with double-bit lock, IP55, HxWxD=1560x1200x270mm, white IP55 surface-mounted service distribution board for damp locations, BPM-O-...Width 1200 mm, outside height 1560 mm, front plate height 1450 mm, depth 270 mm, welded enclosure with door and double-bit lock, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation, door can be right-hand or left-hand door, ample wiring area, open cable entry on top, prepared for F3A gland plate insert, variable interior fittings with or without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, white, RAL 9016

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Surface-mounted installation distribution board with double-bit lock, IP55, HxWxD=1560x1200x270mm, white EL-Nummer (Norway) 0002459528 IP55 surface-mounted service distribution board for damp locations, BPM-O-...Width 1200 mm, outside height 1560 mm, front plate height 1450 mm, depth 270 mm, welded enclosure with door and double-bit lock, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation, door can be right-hand or left-hand door, ample wiring area, open cable entry on top, prepared for F3A gland plate insert, variable interior fittings with or without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1

BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2
BPZ-FPS front plate supports will be additionally required, white, RAL 9016 [Delivery program
Mounting type Surface mounted Material Sheet steel Door interlock Double-ward lock Installation site Moisture-proof
Degree of Protection IP55 Surface finish With powder coating Width 1200 mm Depth 270 mm Height 1560 mm Colour white
(RAL 9016) , Design verification as per IEC/EN 61439
Technical data for design verification Heat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the
enclosure, calculated as per IEC 60890Individual...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-O-1200/15-W with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.