

INDUSTRIAL COMPONENT DATA

BPM-O-600/7 111023 0002459475 EATON ELECTRIC

Surface-mounted installation distribution board with double-bit..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-O-600/7



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-O-600/7
Catalog number	0002459475
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-1018A38203
Generated	2026-08-04

Product Overview

Surface-mounted installation distribution board with double-bit lock, IP55, HxWxDHxWxD=760x600x270mm
IP55 surface-mounted service distribution board for damp locations, BPM-O-...Width 600 mm, outside height 760 mm, front plate height 650 mm, depth 270 mm, welded enclosure with door and double-bit lock, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation, door can be right-hand or left-hand door, ample wiring area, open cable entry on top, prepared for F3A gland plate insert, variable interior fittings with or without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration , 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **EATON - MOELLER**

Additional Product Information

General specifications

Product Name Eaton xEnergy Basic small distribution board Catalog Number 111023 Model Code BPM-O-600/7 EAN 4015081105847 Product Length/Depth 790 mm Product Height 290 mm Product Width 620 mm Product Weight 24.5 kg
Compliances RoHS conform Delivery program
Type Basic device Application Moisture-proof (installation site) Color Light gray (RAL 7035)

Gray Technical data - mechanical

Closure type Other Surface finishing With powder coating Enclosure material Steel Width in number of modular spacings 24

Mounting method Surface mounting

Surface mounted (plaster) Material Sheet steel Number of rows 4 Built-in depth 790 mm Built-in height 290 mm Built-in width 620 mm Cover/door model Closed Cover/door type Double-ward lock

Door

Single Temperature-rise verification as per IEC 60890

Heat diss. ambient 35°C delta T: 20°C wall mount middle encl. top (IEC 60890) 63 W Heat diss. ambient 35°C delta T: 35°C wall mount middle encl. top (IEC 60890) 126 W Heat diss. ambient 35°C delta T:20°C wall mount individ. encl. top (IEC 60890) 71 W Heat diss. ambient 35°C delta T:20°C wall mount starting encl. top (IEC 60890) 67 W Heat diss. ambient 35°C delta T:35°C wall mount individ. encl. top (IEC 60890) 143 W Heat diss. ambient 35°C delta T:35°C wall mount starting encl. top (IEC 60890) 134 W Design verification as per IEC/EN 61439

10.2.2 Corrosion resistance Meets the product standard's requirements. 10.2.3.1 Verification of thermal stability of enclosures Meets the product s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-O-600/7 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.