

INDUSTRIAL COMPONENT DATA

BPM-O-800/12-F 174365 0002455726 EATON ELECTRIC
Surface-mounted installation distribution board without door..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-O-800/12-F



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-O-800/12-F
Catalog number	Y7-174365
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-375A46E7F2
Generated	2026-08-05

Product Overview

Surface-mounted installation distribution board without door, IP55, HxWxD=1260x800x270mm
IP55 surface-mounted service distribution board for damp locations without door, BPM-O-...Width 800 mm, outside height 1260 mm, front plate height 1150 mm, depth 270 mm, welded enclosure, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation, door can be right-hand or left-hand door, ample wiring area, open cable entry on top, prepared for F3A gland plate insert, variable interior fittings with or without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

EL-Nummer (Norway)0002455726Surface-mounted installation distribution board without door, IP55, HxWxD=1260x800x270mmIP55 surface-mounted service distribution board for damp locations without door, BPM-O-...Width 800 mm, outside height 1260 mm, front plate height 1150 mm, depth 270 mm, welded enclosure, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation, door can be right-hand or left-hand door, ample wiring area, open cable entry on top, prepared for F3A gland plate insert, variable interior fittings with or without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1

BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2
BPZ-FPS front plate supports will be additionally required, gray, RAL 7035
Delivery program
Mounting typeSurface mountedFeatureswithout doorMaterialSheet steelInstallation siteMoisture-proofDegree of
ProtectionIP55Surface finishWith powder coatingWidth800 mmDepth270 mmHeight1260 mmColourlight gray (RAL
7035)Design verification as per IEC/EN 61439
Technical data for design verificationHeat dissipation, at an ambient temperature of 35°C, delta T: 20 degrees in top of the
enclosure, calculated as per IEC 60890Individual enclosure for wall mounting [PV]122 WHeat dissipation, at an ambient t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-O-800/12-F with the required quantity to info@electricaonline.com or use
electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd
Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification
requirements against the manufacturer documentation before purchase or installation.