

INDUSTRIAL COMPONENT DATA

BPM-O-800/15-F 174366 Y7-174366 EATON ELECTRIC

Surface-mounted installation distribution board without door,..

Brand: EATON - MOELLER | Manufacturer Part Number: BPM-O-800/15-F



Manufacturer	EATON - MOELLER
MPN / Reference	BPM-O-800/15-F
Catalog number	Y7-174366
Category	Small distribution board
Minimum order	1 Pcs
Document ID	EO-443AADA508
Generated	2026-08-06

Product Overview

Surface-mounted installation distribution board without door, IP55, HxWxD=1560x800x270mm

BPM-O-800/15-F

IP55 surface-mounted service distribution board for damp locations without door, BPM-O-...Width 800 mm, outside height 1560 mm, front plate height 1450 mm, depth 270 mm, welded enclosure, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation, door can be right-hand or left-hand door, ample wiring area, open cable entry on top, prepared for F3A gland plate insert, variable interior fittings with or without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration , 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER > Enclosures
--------------	------------------------------

Additional Product Information

Surface-mounted installation distribution board without door, IP55, HxWxD=1560x800x270mmIP55 surface-mounted service distribution board for damp locations without door, BPM-O-...Width 800 mm, outside height 1560 mm, front plate height 1450 mm, depth 270 mm, welded enclosure, earthed metal covers, extraordinary stability as a result of welded construction, well-structured, multilayered design for easily accessible installation, door can be right-hand or left-hand door,

ample wiring area, open cable entry on top, prepared for F3A gland plate insert, variable interior fittings with or without removable mounting frame, indoor installation with MSW or mounting towers possible, if using an MSW assembly configuration, 2 pairs of BPZ-CTS-S corner towers and 1 BPZ-SNAP-MSW-CTS snap fitting element will be additionally required, if using a base frame assembly configuration, 2 BPZ-FPS front plate supports will be additionally required, gray, RAL 7035

General specifications
Product name Eaton xEnergy Basic small distribution board
Part no. BPM-O-800/15-FEAN4015081708284
Product Length/Depth 270 millimetre
Product height 1560 millimetre
Product width 800 millimetre
Product weight 43.8 kilogram
Compliances RoHS conform
Product Tradename xEnergy Basic
Product Type Small distribution board
Product Sub Type None
Delivery program Type Basic device
Application Moisture-proof (installation site)
Color Gray
Light gray (RAL 7035)
Technical Data - Mechanical
Closure type Other
Surface finishing With powder coating
Enclosure mate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / BPM-O-800/15-F with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.