

INDUSTRIAL COMPONENT DATA

SPB-12/280/4 285082 SPET2-280/4 EATON ELECTRIC Power Distribution Components IEC Miniature circuit breaker

Brand: EATON - MOELLER | Manufacturer Part Number: SPB-12/280/4



Manufacturer	EATON - MOELLER
MPN / Reference	SPB-12/280/4
Catalog number	SPET2-280/4
Category	Combined arrester for power supply systems
Minimum order	1 Pcs
Document ID	EO-318938B0F4
Generated	2026-08-03

Product Overview

Power Distribution Components IEC Miniature circuit breaker

Surge arrester, 4p, 280VAC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	EATON - MOELLER
--------------	-----------------

Additional Product Information

Surge arrester complete, 4-pole, 280VAC, 4x10kA Alternate Catalog No. SPET2-280/4 For protecting consumer systems against transient overvoltages caused by indirect lightning strikes and switching operations, test class II according to IEC 61643-1+A1, SPD-type T2 according to EN 61643-11, can be bussed with all Xtra Combinations switchgear, use in accordance with IEC 60364-5-53 clause 534 [Delivery program

Products Surge arresters Application field Residential buildings

Utility buildings

Open areas , Technical data ETIM 7.0

Earthing, lightning and surge protection (EG000021) / Surge protection device for power supply systems (EC000941)

Electric engineering, automation, process control engineering / Protection installation, device (electric) / Surge protection device (inner lightning protection) / Surge protection device for power supply systems ( [ACN278011])

System configuration DC No System configuration IT No System configuration TN No System configuration TN-C No

System configuration TN-C-S No System configuration TN-S No System configuration TT No System configuration other

Yes Number of conductors (without earthing) 4 Nominal discharge surge current (8/20) 10 kA Nominal voltage AC 280 V

Nominal voltage DC 0 V Short-circuit breaking capacity (Iscrr) 0 kA Max. continuous voltage AC 280 V Max. discharge

surge current (8/20) 20 kA Max. continuous voltage DC 0 V Mounting method DIN rail (top hat rail) 35 mm Construction size 4 modular spacing Max. PV-voltag...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send EATON - MOELLER / SPB-12/280/4 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.